



Datenblatt - Fiche technique - Data sheet

12.02.1006



ROLINE RS232 nach RS422/485 Konverter für DIN Hutschiene, Professional

ROLINE Adaptateur RS232 vers RS422/485 pour rail DIN, Pro

ROLINE Converter RS-232 to RS-422/485, with Isolation, for DIN Rail,
Professional

Item no. 12.02.1006

ROLINE RS232-RS422/485 Converter, w/Isolation, DIN Rail, Professional



Features:

- RS-422/RS-485 transceiver
- Transmission Speed (bps): 300 ~ 115,200 (RS-232 and RS-422/485 can set to different baud rate)
- **Auto direction flow control on RS-485**
- Addressable and non-addressable mode configurable
- High isolation voltage up to 3000VDC
- Connectors: RS-232: DB9 Female, RS-422/485: 7-pin terminal block
- Signals: RXD, TXD, RTS, CTS, for RS-232
TX+, TX-, RX+, RX- for RS-422
DATA+, DATA- for RS-485
- Surge protection on RS-422/485 lines
- Built-in microprocessor
- Watchdog timer function included
- All communication setups stored in EEPROM
- Power and data flow indicator for troubleshooting
- Power Requirement: +10V to +30VDC Unregulated with against power