



Datenblatt - Fiche technique - Data sheet

14.99.3222



VALUE 19" KVM-Umschalter 1 User - 8 PCs (PS/2+USB)

VALUE Commutateur 19", 1 Util. - 8 PCs (PS/2+USB)

VALUE 19" KVM Switch with OSD, 1 User - 8 PCs, PS/2+USB

Technical Specifications 14.99.3222

Feature	Specification	
KVM Type	PS/2 Console KVM	USB Console KVM
Console Ports	One Local PS/2 console	One Local USB console plus One Optional Remote Module
PC Port Connector	VGA	
PC Ports	8/16	
Max. Distance (KVM switch -- Host)	16 feet (5.0m)	
Video Resolution (Local Console)	1920 x 1440	
Video Resolution (Remote Console)	1600 x 1200 for CAT5-Based 500 feet remote console. 1024 x 768 for CAT5-Based 1000 feet remote console. 1600 x 1200 for IP-Based remote console	
CAT5-Based Remote Console Module	RJ-45 Connector, CAT.5 console up to 1000 feet away from KVM switch with superior, auto-adjust RGB gain/delay control capability	
IP-Based Remote Module	RJ-45 8P8C for 10/100 M Ethernet, DB9 male for Modem, Null modem and serial power control, Mini USB 2.0 receptacle	
Daisy Chaining	Support Daisy Chaining with both Bus (8-layer) and Tree (2-layer) topologies, DB15 Female Connector	
Computer port selection	On Screen Display (OSD) Menu, Hot Key, Push Button	
Hotkey	Provide various Hotkey (Scroll-Lock/ Cap-Lock/ Num-Lock/ Alt/ Ctrl/ Win)	
PC Port LEDs	2x LEDs per PC port: Power (Red), Online (Blue)	
7-seg LED for Bank display	1 set	
Security	Provide ACL (Access Control List) security function, store up to 8 independent controllable Computers lists	
Multilingual OSD (On Screen Display) control	8 languages (English, France, German, Spanish, Italian, Russian, Japanese, Simplified Chinese)	
Auto-Scan Intervals	5 ~ 99 Sec.	
Keyboard Emulation	PS/2 or USB	
Mouse Emulation	PS/2 or USB	
Max. PC Connection	>1024	
Housing	Metal	
Power	DC Power adapter : 12V DC, 1A	
Operation Temperature	0 ~ 50°C	
Storage Temperature	-20 ~ 60°C	
Humidity	0~95%, Non-Condensing	
Mechanical	19" Rack mount, 1U	
Dimension (mm)	444.5 * 160 * 44.3	