

# **PRODUCT DATASHEET**RF GLOBE 60 7 W/827 E27 FIL

LED Retrofit CLASSIC GLOBE | LED lamps, classic ball shape



#### **AREAS OF APPLICATION**

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires
- Perfect for decorative installations

#### **PRODUCT BENEFITS**

- Very low energy consumption
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Design, dimensions, luminous flux comparable to an incandescent lamp
- Clear lamps with innovative LED "filament" technology

#### **PRODUCT FEATURES**

- LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Lifetime: up to 15,000 h
- Beam angle: up to 360°
- Energy efficiency class: A++



# **TECHNICAL DATA**

# Electrical data

| Rated wattage                          | 7.00 W   |
|--|----------|
| Nominal wattage                        | 7.00 W   |
| Nominal voltage                        | 220240 V |
| Operating frequency                    | 5060 Hz  |
| Power factor λ                         | > 0.50   |
| Claimed equiv. conventional lamp power | 60 W     |

# Photometrical data

| Nominal luminous flux                   | 806 lm     |  |
|---|------------|--|
| Rated luminous flux                     | 806 lm     |  |
| Rated color temperature                 | 2700 K     |  |
| Color rendering index Ra                | ≥80        |  |
| Lumen main.fact.at end of nom.life time | 0.70       |  |
| Light color (designation)               | Warm White |  |
| Standard deviation of color matching    | ≤6 sdcm    |  |

# Light technical data

| Warm-up time (60 %) | < 0.50 s |
|---------------------|----------|
| Starting time       | < 0.5 s  |

# Dimensions & weight



| Overall length | 173.0 mm |
|----------------|----------|
| Diameter       | 125.0 mm |
| Outer bulb     | G125     |
| Length         | 173.0 mm |

# Lifespan

| Nominal lamp life time                   | 15000 h |
|--|---------|
| Rated lamp life time                     | 15000 h |
| Number of switching cycles               | 100000  |
| Lumen maintenance at end of service life | 0.70    |

#### Additional product data

| Base (standard designation) | E27  |  |  |
|-----------------------------|--|--|--|
| Mercury content             | 0.0 mg   |  |  |
| Mercury-free                | Yes  |  |  |
| Design / version            | Clear  |  |  |
| Show WEEE picto             | Yes  |  |  |
| Product remark              | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |  |  |

#### Capabilities

#### Certificates & standards

| Energy efficiency class | A++         |
|-------------------------|-------------|
| Energy consumption      | 7 kWh/1000h |

#### Country specific categorizations

| ILCOS           | DRAG/C-6/827-220-240-E27-124 |  |
|-----------------|------------------------------|--|
| Order reference | LEDSG12560 7W/8              |  |

#### **LOGISTICAL DATA**

| Product code  | Product description            | Packaging unit<br>(Pieces/Unit) | Dimensions (length x width x height) | Volume    | Gross weight |
|---------------|--------------------------------|---------------------------------|--------------------------------------|-----------|--------------|
| 4052899972377 | RF GLOBE 60 7 W/827<br>E27 FIL | Shipping carton box<br>4        | 291 mm x 291 mm x<br>228 mm          | 19.31 dm³ | 1284.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.