

# PRODUCT DATASHEET

## ST R80 71 36° 5 W/827 E27

LED STAR R80 | LED reflector lamps R80 with retrofit screw base



### AREAS OF APPLICATION

- Display cabinets and shop windows
- Museums, art galleries
- Hospitality
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Outdoor applications only in suitable luminaires

### PRODUCT BENEFITS

- Long lifetime of up to 15,000 h
- Low energy consumption
- Easy replacement of halogen lamps thanks to compact design
- Instant 100 % light, no warm-up time

### PRODUCT FEATURES

- Professional LED alternative to halogen lamps
- Mercury-free lamps



## TECHNICAL DATA

### Electrical data

Rated wattage	5.00 W
Nominal wattage	5.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	71 W
Operating frequency	50...60 Hz
Power factor $\lambda$	> 0.50


### Photometrical data

Luminous intensity	970 cd
Nominal luminous flux	390 lm
Rated luminous flux	390 lm
Rated color temperature	2700 K
Color rendering index Ra	$\geq 80$
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Standard deviation of color matching	$\leq 6$ sdcn
Nominal useful luminous flux 90°	390 lm
Rated useful luminous flux 90°	390 lm
Rated peak intensity	970 cd
Nom. useful luminous flux 120°	405 lm
Rated useful luminous flux 120°	405 lm

### Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s
Nominal beam angle	36 °
Rated beam angle (half peak value)	36.00 °

## Dimensions & weight



Overall length	110.0 mm
Diameter	80.0 mm
Outer bulb	R80
Length	110.0 mm
Maximum diameter	80.0 mm

## Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000

## Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Show WEEE picto	Yes
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

## Capabilities

Dimmable	No
----------	----

## Certificates & standards

Energy efficiency class	A+
Energy consumption	5 kWh/1000h

## Country specific categorizations

<b>ILCOS</b>	DRR-5/827-220-240-E27-80/36
<b>Order reference</b>	SR807136 5W/827

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899963603	ST R80 71 36° 5 W/827 E27	Shipping carton box 6	500 mm x 154 mm x 201 mm	15.48 dm <sup>3</sup>	863.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## REFERENCES / LINKS

For further products and actual information concerning LED lamps see

- ▶ [www.ledvance.com/ledlamps](http://www.ledvance.com/ledlamps)

For Guarantee see

- ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.