

# PRODUCT DATASHEET

## SubMARINE 8 W 40 4000 K

SubMARINE | Luminaires



---

### AREAS OF APPLICATION

- Basements, garages, warehouses
- For indoor use only

---

### PRODUCT BENEFITS

- Optimal electrical protection thanks to two security components
- Energy savings of up to 65 % comp. to luminaires using T8 fluorescent lamps on CCG
- Good, even illumination
- Quick and easy lamp replacement

---

### PRODUCT FEATURES

- Color rendering index  $R_a : \geq 80$
- Color temperature: 4,000 K
- Damp-proof luminaire with LED tube for mains voltage operation
- Durable and energy-saving LED luminaire
- Protection class: I
- PG cable gland on the side
- Fire and ignition resistant housing acc. to EN 60598-1, 650 °C Glow Wire Test
- Robust polycarbonate casing



- Lifetime: up to 30,000 h
- Mercury-free and RoHS compliant
- Not dimmable
- Dust-protected and jet-proof (IP65)

## TECHNICAL DATA

### Electrical data

Nominal wattage	8.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

### Photometrical data

Color temperature	4000 K
Luminous flux	720 lm
Light color (designation)	Cool White
Color rendering index Ra	>80

### Dimensions & weight



Length	655.0 mm
Width	72.0 mm
Height	86.0 mm
Product weight	783.00 g

### Colors & materials

Body material	Polycarbonate (PC)
Product color	Gray
Cover material	Polycarbonate (PC)

### Temperatures & operating conditions

Ambient temperature range	-20...45 °C
---------------------------	-------------

## Lifespan

<b>Lifespan</b>	30000 h
-----------------	---------

## Capabilities

<b>Type of installation</b>	Surface mounting
<b>Dimmable</b>	No
<b>Type of connection</b>	Terminal, 3-pin
<b>Holder designation</b>	G13

## Certificates &amp; standards

<b>Protection class</b>	I
<b>Type of protection</b>	IP65
<b>Standards</b>	CE/Acc. to IEC 60598-1/RoHS/REACH/Acc. to IEC 62471

## EQUIPMENT / ACCESSORIES

- SubstiTUBE STAR EM and SubstiTUBE Start are delivered with the product

## SAFETY ADVICE

Installation by qualified electrician only.

Luminaire must be disconnected from mains during installation, maintenance and cover removal

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899398269	SubMARINE 8 W 40 4000 K	Shipping carton box 10	670 mm x 190 mm x 360 mm	45.83 dm <sup>3</sup>	9080.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.