

PRODUCT DATASHEET

SubMARINE 17 W 40 4000 K

SubMARINE | Luminaires

AREAS OF APPLICATION

- Basements, garages, warehouses
- For indoor use only



PRODUCT BENEFITS

- Optimal electrical protection thanks to two security components
- Energy savings of up to 65 % comp. to luminaires using T8 fluorescent lamps on CCG
- Good, even illumination
- Quick and easy lamp replacement

PRODUCT FEATURES

- Color rendering index $R_a : \geq 80$
- Color temperature: 4,000 K
- Damp-proof luminaire with LED tube for mains voltage operation
- Durable and energy-saving LED luminaire
- Protection class: I
- PG cable gland on the side
- Fire and ignition resistant housing acc. to EN 60598-1, 650 °C Glow Wire Test
- Robust polycarbonate casing



- Lifetime: up to 30,000 h
- Mercury-free and RoHS compliant
- Not dimmable
- Dust-protected and jet-proof (IP65)

TECHNICAL DATA


Electrical data

Nominal wattage	17.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 K
Luminous flux	1550 lm
Light color (designation)	Cool White
Color rendering index Ra	>80

Dimensions & weight



Length	1265 mm
Width	72.0 mm
Height	86.0 mm
Product weight	1324.00 g

Colors & materials

Body material	Polycarbonate (PC)
Product color	Gray
Cover material	Polycarbonate (PC)

Capabilities

Type of installation	Surface mounting
-----------------------------	------------------

Dimmable	No
Type of connection	Terminal, 3-pin
Holder designation	G13

Certificates & standards

Protection class	I
Type of protection	IP65
Standards	CE/Acc. to IEC 60598-1/RoHS/REACH/Acc. to IEC 62471

EQUIPMENT / ACCESSORIES

- SubstiTUBE STAR EM and SubstiTUBE Start are delivered with the product

SAFETY ADVICE

Installation by qualified electrician only.

Luminaire must be disconnected from mains during installation, maintenance and cover removal

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899398283	SubMARINE 17 W 40 4000 K	Shipping carton box 9	1285 mm x 275 mm x 220 mm	77.74 dm ³	13328.00 g
4052899398283	SubMARINE 17 W 40 4000 K	Shipping carton box 9	1285 mm x 275 mm x 220 mm	77.74 dm ³	13343.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.