

PRODUCT DATASHEETLUNIVE VELA 19 W C40 4000 K

LUNIVE | Luminaires with glass cover



AREAS OF APPLICATION

- Indoor applications
- Dining rooms, living rooms, study rooms
- Corridors

PRODUCT BENEFITS

- Available in two light colors to create the right atmosphere in your room
- Very homogenous light
- Quick and simple installation
- 5 years guarantee

PRODUCT FEATURES

- Ceiling luminaire with advanced LED technology
- Italian designs, available in various sizes and wattages
- High quality glass and metal housing finish



TECHNICAL DATA


Electrical data

Operating mode	Mains voltage	
Nominal wattage	19.00 W	
Nominal voltage	220240 V	
Mains frequency	50/60 Hz	

Photometrical data

Color temperature	4000 K	
Luminous flux	1050 lm	
Light color (designation)	Cool White	
Color rendering index Ra	>80	

Dimensions & weight



Length	305.0 mm
Width	305.0 mm
Height	75.0 mm
Product weight	1540.00 g

Colors & materials

Body material	Metal
Product color	Gray/White
Cover material	Glass

Lifespan

Lifespan	20000 h
----------	---------

Capabilities

Dimmable	No
----------	----

Type of connection	Push and screw terminal	

Certificates & standards

Protection class	1
Type of protection	IP20
Standards	CE/REACH/RoHS

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899373662	LUNIVE VELA 19 W C40 4000 K	Shipping carton box 2	351 mm x 342 mm x 228 mm	27.37 dm³	3982.00 g
4052899373662	LUNIVE VELA 19 W C40 4000 K	UN4 1	463 mm x 454 mm x 171 mm	35.94 dm³	2141.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.