

PRODUCT DATASHEETST CLAS A 60 7 W/840 E27

LED Retrofit CLASSIC A | LED lamps, classic bulb shape

AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires
- Perfect for decorative installations

PRODUCT BENEFITS

- Clear lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)
- Correct operation even at low temperatures

PRODUCT FEATURES

- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Lifetime: up to 15,000 h



- Beam angle: up to 300°

TECHNICAL DATA

Electrical data

| Rated wattage | 7.00 W |
|--|----------|
| Nominal wattage | 7.00 W |
| Nominal voltage | 220240 V |
| Operating frequency | 5060 Hz |
| Power factor λ | > 0.50 |
| Claimed equiv. conventional lamp power | 60 W |


Photometrical data

| Nominal luminous flux | 806 lm |
|---|------------|
| Rated luminous flux | 806 lm |
| Rated color temperature | 4000 K |
| Color rendering index Ra | ≥80 |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Cool White |
| Standard deviation of color matching | ≤6 sdcm |

Light technical data

| Warm-up time (60 %) | < 0.50 s |
|---------------------|----------|
| Starting time | < 0.5 s |

Dimensions & weight



| Overall length | 105.0 mm |
|----------------|----------|
| Diameter | 60.0 mm |
| Outer bulb | A60 |
| Length | 105.0 mm |

Lifespan

| Nominal lamp life time | 15000 h |
|--|---------|
| Rated lamp life time | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service life | 0.70 |

Additional product data

| Base (standard designation) | E27 | | |
|-----------------------------|--|--|--|
| Mercury content | 0.0 mg | | |
| Mercury-free | Yes | | |
| Design / version | Frosted | | |
| Show WEEE picto | Yes | | |
| Product remark | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value | | |

Capabilities

| Dimmable | No |
|----------|----|
|----------|----|

Certificates & standards

| Energy efficiency class | A++ | |
|-------------------------|-------------|--|
| Energy consumption | 7 kWh/1000h | |

Country specific categorizations

| ILCOS | DRAA/F-7-840-220-240-E27-60 | |
|-----------------|-----------------------------|--|
| Order reference | LEDSCLA60 7W/84 | |

LOGISTICAL DATA

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-----------------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4058075078307 | ST CLAS A 60 7 W/840 E27 | Shipping carton box 18 | 377 mm x 148 mm x 201 mm | 11.21 dm³ | 885.00 g |
| 4058075808393 | ST CLAS A 60 7 W/840 E27 | Shipping carton box 6 | 381 mm x 153 mm x 136 mm | 7.93 dm ³ | 421.00 g |
| 4058075808409 | ST CLAS A 60 7 W/840 E27 | Shipping carton box 12 | 377 mm x 148 mm x 201 mm | 11.21 dm³ | 673.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.