

PRELIMINARY-PRODUCT DATASHEET DoorLED Down Silver

Door LED Down | Mobile luminaire for entrance areas, light outlet down



AREAS OF APPLICATION

- For a very large range of uses
- Indoor and outdoor
- Entrance lighting
- Corridors
- Patios, balconies

PRODUCT BENEFITS

- Attractive and functional design
- Economical operation due to low power consumption
- Easy and quick installation
- All accessories for flexible mounting options included

PRODUCT FEATURES

- Integrated light and motion sensor
- Available in two housing colors
- Type of protection: IP54



TECHNICAL DATA


Electrical data


Operating mode	Battery	
Nominal wattage	0.95 W	
Nominal voltage	NaN V	
Mains frequency	0 Hz	

Photometrical data

Color temperature	4000 K	
Luminous flux	40 lm	
Light color (designation)	Cool White	
Color rendering index Ra	>80	

Dimensions & weight





Length	102.5 mm
Width	92.4 mm
Height	36.5 mm
Product weight	154.00 g

Colors & materials

Body material	Polycarbonate (PC)	
Product color	Silver	

Temperatures & operating conditions

Ambient temperature range	025 °C

Lifespan

_		
I	Lifespan	25000 h

Capabilities

Dimmable	No	
Type of sensor	Passive infrared (PIR)	

Certificates & standards

Protection class	III	
Type of protection	IP54	
Standards	CE	

EQUIPMENT / ACCESSORIES

- Batteries included: 4x 1.5 V LR6 (AA)

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075027299	DoorLED Down Silver	Blister 1	39 mm x 140 mm x 195 mm	1.06 dm³	178.00 g
4058075027305	DoorLED Down Silver	Shipping carton box 6	247 mm x 154 mm x 210 mm	7.99 dm³	1195.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.