

PRELIMINARY-PRODUCT DATASHEET SubMARINE Integrated 48 W

SubMARINE Integrated | Damp-proof luminaires with integrated LED module

AREAS OF APPLICATION

- Basements, garages, warehouses



PRODUCT BENEFITS

- Easy and quick installation
- Very homogenous light
- 3 years quarantee
- Extremely bright

PRODUCT FEATURES

- Dust-protected and jet-proof (IP65)
- Not dimmable



TECHNICAL DATA

Electrical data

Operating mode	Integrated LED driver	
Nominal wattage	48.00 W	
Nominal voltage	220240 V	
Mains frequency	50/60 Hz	

Photometrical data

Color temperature	4000 K
Luminous flux	4000 lm
Light color (designation)	Cool White
Color rendering index Ra	>80

Dimensions & weight



Length	1480 mm
Width	86.0 mm
Height	72.0 mm
Product weight	1580.00 g

Colors & materials

Body material	Polycarbonate (PC)	
Product color	Gray	

Temperatures & operating conditions

Ambient temperature ran	-2035 °C	

Capabilities

Certificates & standards

Protection class	II
Type of protection	IP65
Standards	CE/REACH/RoHS

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075026506	SubMARINE Integrated 48 W	Shipping carton box 8	1530 mm x 200 mm x 328 mm	100.37 dm ³	15560.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.