PRODUCT DATASHEET
SILARA PURE 300 16 W 830

SILARA Pure | LED ceiling luminaires

AREAS OF APPLICATION

– For indoor use only
– Decorative domestic lighting
– Ceiling and wall surface mounting

PRODUCT BENEFITS

– Very homogenous light
– Easy and quick installation

PRODUCT FEATURES

– Ceiling luminaire with advanced LED technology
– Circular light emission

TECHNICAL DATA

Electrical data

Operating mode	Integrated LED driver
Nominal wattage	16.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Luminous flux	1100 lm
Light color (designation)	Warm White
Color rendering index Ra	>80

Dimensions & weight

Diameter	300.0 mm
Height	85.0 mm
Product weight	495.00 g

Colors & materials

Body material	Metal
Product color	White

Lifespan

Lifespan	25000 h

Capabilities

Dimmable	No

Certificates & standards

Protection class	I
Type of protection	IP20
Standards	CE/REACH/RoHS

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075032897	SILARA PURE 300 16 W 830	Shipping carton box 6	687 mm x 382 mm x 360 mm	94.48 dm³	6315.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

—