

PRODUCT DATASHEETENDURA STYLE Shield RD 11 W DG

ENDURA STYLE SHIELD | Luminaires with modern design and light outlet up and down



AREAS OF APPLICATION

- Outdoor
- Building facades
- Entrance lighting

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP44
- Die-cast aluminum housing
- Available in round and square form



TECHNICAL DATA


Electrical data

Operating mode	Mains voltage	
Nominal wattage	10.50 W	
Nominal voltage	220240 V	
Mains frequency	50/60 Hz	

Photometrical data

Color temperature	000 K	
Luminous flux	400 lm	
Light color (designation)	Warm White	
Color rendering index Ra	>80	

Dimensions & weight



Length	60.0 mm
Width	240.0 mm
Height	142.0 mm
Product weight	710.00 g

Colors & materials

Body material	Aluminum	
Product color	DARK GRAY	
Cover material	Polymethylmethacrylate (PMMA)	

Temperatures & operating conditions

Ambient temperature range	-2040 °C
---------------------------	----------

Lifespan

_		
	Lifespan	30000 h

Capabilities

Dimmable	No
----------	----

Certificates & standards

Protection class	l .
Type of protection	IP44
Standards	CE

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075031739	ENDURA STYLE Shield RD 11 W DG	Shipping carton box 6	600 mm x 220 mm x 290 mm	38.28 dm³	6531.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.