

PRODUCT DATASHEET ENDURA STYLE Cylinder Wall 6 W ST

ENDURA STYLE CYLINDER | Stainless steel wall-luminaires and bollards with indirect illumination



AREAS OF APPLICATION

- Outdoor
- Building facades
- Gardens, balconies and other outdoor areas
- Pathway lighting
- Driveways

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP44
- Housing made of Polycarbonate covered with stainless steel
- Available as wall, ceiling and bollard luminares



TECHNICAL DATA


Electrical data

Operating mode	Mains voltage
Nominal wattage	6.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 К
Luminous flux	360 lm
Light color (designation)	Warm White
Color rendering index Ra	>80

Dimensions & weight



Length	138.0 mm
Width	102.0 mm
Height	135.0 mm
Product weight	470.00 g

Colors & materials

Body material	Stainless steel	
Product color	STEEL	

Temperatures & operating conditions

Ambient temperature range	-2040 °C
Capabilities	
Dimmable	No
Certificates & standards	

Protection class	П
Type of protection	IP44

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075032545	ENDURA STYLE Cylinder Wall 6 W ST	Shipping carton box 6	380 mm x 175 mm x 320 mm	21.28 dm³	4158.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.