

PRODUCT DATASHEET NOXLITE LED SPOT Sensor 2X8 W 3000 K GR

NOXLITE LED SPOT Sensor | Outdoor LED wall luminaires



AREAS OF APPLICATION

- Outdoor
- Garages
- Patios, balconies

PRODUCT BENEFITS

- Functional design
- High light output thanks to high-power LED
- Quick and simple installation
- Compact and lightweight

PRODUCT FEATURES

- Very bright and functional outdoor LED luminaires
- Motion and day/night sensor with time settings from 5 s...10 min
- Type of protection: IP44
- Adjustable (down 70°, left/right 30°)



IP 44







TECHNICAL DATA

Electrical data

Operating mode	ECG
Nominal wattage	17 W
Nominal voltage	100240 V
Mains frequency	5060 Hz

Photometrical data

Color temperature	3000 K	
Luminous flux	400 lm	
Light color (designation)	Warm white	
Color rendering index Ra	>80	

Dimensions & weight

Length	170.0 mm
Width	180.0 mm
Height	90.0 mm
Product weight	503.00 g

Colors & materials

Product color	Anthracite
	Anthracite

Temperatures & operating conditions

Ambient temperature range	-20+40 °C

Additional product data

Number of lighting outlets	2
----------------------------	---

Capabilities

Type of installation	Direct mounting/Surface-mounted	
Dimmable	No	
Type of connection	Terminal, 2-pole, max. 2,5 mm ²	

Certificates & standards

Protection class	II IP44	
Type of protection		
Standards	CE	

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899193369	NOXLITE LED SPOT Sensor 2X8 W 3000 K GR	Folding carton box 1	218 mm x 115 mm x 255 mm	6.39 dm³	861.00 g
4052899193376	NOXLITE LED SPOT Sensor 2X8 W 3000 K GR	Shipping carton box 4	457 mm x 256 mm x 285 mm	33.34 dm ³	3995.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.