

PRODUCT DATASHEETNOXLITE CIRCULAR 20 W SENSOR

NOXLITE LED Circular | Outdoor LED wall luminaires



AREAS OF APPLICATION

- Outdoor
- Foyers
- Facade and building illumination
- Humid conditions in interior and semi-exterior applications
- Garages

PRODUCT BENEFITS

- Impressive for its low-profile design
- Pleasant homogenous light
- High-quality materials
- Creates a pleasant, calm atmosphere

PRODUCT FEATURES

- Surface-mounted luminaire with direct/indirect lighting
- Type of protection: IP44
- Coated steel casing
- Protection class: I



IK 06 IP 44 ((







TECHNICAL DATA

Electrical data

Operating mode	ECG
Nominal wattage	21.5 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Luminous flux	930 lm
Light color (designation)	Warm white
Color rendering index Ra	>80

Dimensions & weight

Diameter	298.0 mm
Height	70.0 mm
Product weight	1180.00 g

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Additional product data

Equipped with lamp	Yes
-4mphon	. 65

Capabilities

Type of installation Direct mounting/Surface-mounted	
Adjustable	No
Dimmable	No
Type of connection	Terminal, 3-pole

Certificates & standards

Protection class	I
Type of protection	IP44
Standards	CE

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899905634	NOXLITE CIRCULAR 20 W SENSOR	Folding carton box 1	351 mm x 306 mm x 103 mm	11.06 dm³	1485.00 g
4052899905696	NOXLITE CIRCULAR 20 W SENSOR	Shipping carton box 2	358 mm x 324 mm x 227 mm	26.33 dm³	3652.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.