



Datenblatt - Fiche technique - Data sheet

21.13.1072



ROLINE Fast Ethernet Konverter, RJ-45 - ST

ROLINE Convertisseur Fast Ethernet, RJ45-ST

ROLINE Fast Ethernet Converter, RJ-45 to ST

Item no.: 21.13.1072

ROLINE 10/100Mbps Fast Ethernet Converter, RJ-45-ST



Features:

- Support full wire speed conversion for 10/100Mbps speed and media types
- Transparent conversion to 802.1Q VLAN tagged packets
- Low power consumption, 1.8W max. @+3.3V
- Support DIN rail mounting and wall mounting
- TP port: IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
 - Shielded RJ-45 jacks with auto MDI/MDI-X detection
 - Auto-negotiation for speed and duplex auto detection
 - Speed for 10/100Mbps, Full/half-duplex support
- FX port: IEEE 802.3u 100Base-FX compliant
 - Forced 100Mbps, Full-duplex
 - Far end fault function
- Cable: 10/100Base-TX: Cat. 5 UTP cable
 - 100Base-FX: MMF 62.5/125pm, 50/125pm
- LEDs: TP speed, Link/Activity, Power status
- Packet Size: Up to 1536 bytes
- Environment: Operating Temperature: 0°C ~ 40°C
 - Storage Temperature: -30°C ~ 80°C
 - Relative Humidity: 5% ~ 95% non-condensing
- Dimension: 64 x 59 x 21 mm (WxDxH)
- Power input: +3.3VDC via external power adapter
- Fiber connector: Duplex ST