

Product Highlights

Connect and Power PoE Devices

4 Power-over-Ethernet (PoE) ports allow you to connect and power PoE-capable cameras, access points, and VoIP phones using just Ethernet cabling

PoE+ Support with 68W PoE Power Budget

802.3at PoE (up to 30 watts per port) with a high PoE power budget (up to 68 watts total), ideal for 802.11ac wireless access points and multi-featured network cameras

Gigabit Ethernet Speed

High-speed ports with Gigabit connectivity with full backwards compatibility for connections to older computers and equipment



DGS-1008P

8-Port Gigabit PoE Unmanaged Desktop Switch

Features

High-Speed Networking

- Eight 10/100/1000 Mbps Gigabit Ethernet ports
- Full/Half-duplex for Ethernet/Fast Ethernet/Gigabit Ethernet speeds

Reliability

- IEEE 802.3x flow control
- Store-and-forward switching scheme
- RoHS compliant

Easy Setup

- Plug-and-Play installation
- Auto MDI/MDI-X crossover for all ports
- Ports located conveniently at the rear
- Noise-free operation

The DGS-1008P 8-Port Gigabit PoE Unmanaged Desktop Switch enables both home and office users to easily connect and supply power to Power over Ethernet (PoE) devices such as wireless Access Points (APs), IP cameras, and IP phones while adding more Ethernet devices like computers, printers, and Network Attached Storage (NAS) onto a network. Built with home and small business users in mind, this compact PoE switch operates quietly, making it ideal for use in virtually any room or office.

Power over Ethernet

The DGS-1008P features 4 10/100/1000BASE-T ports that support the IEEE 802.3at PoE protocol. Each of the 4 PoE ports can supply up to 30 Watts, for a total PoE budget of 68 Watts, allowing users to attach an IEEE 802.3at-compliant device to the DGS-1008P without requiring additional power. PoE is especially suitable for devices that are far from power outlets or when you want to minimise the clutter of extra cables. When a device is not PoE-compatible, the D-Link DWL-P50 PoE Adapter can turn any regular Ethernet port into a PoE Ethernet port.

Superior Performance

No configuration is required and installation is quick and easy. Support for Auto MDI/MDI-X on all ports eliminates the need for crossover cables when connecting to another switch or hub. Auto-Negotiation on each port senses the link speed of a network device (either 10, 100 or 1000) and intelligently adjusts for compatibility and optimal performance. The switch has been designed without fans so you can be sure of quiet operation wherever it is installed. The DGS-1008P also features diagnostic LEDs, which display status and activity, allowing you to quickly detect and correct problems on the network. With wire-speed filtering and store-and-forward switching, the DGS-1008P also maximises network performance while minimising the transmission of bad network packets. Combining the convenience of PoE, superior performance, and ease of use, the 8-Port Gigabit PoE Unmanaged Desktop Switch is the ideal choice for adding PoE devices to either a home or small business network.


Hassle-free Setup

The 8-Port Gigabit PoE Unmanaged Desktop Switch is a Plug-and-Play device that requires no configuration, so setup is simple and hassle-free. But we know that setting up your switch is only the beginning; you may want to connect multiple computers, share files, music, and video across your home or small office network, or even create a multi-player gaming environment. That's why D-Link provides a support website to answer all of your questions and help you get the most out of your network. Find answers to frequently asked questions, download product updates, and easily access the friendly D-Link Customer Support Team.

Compact and Silent

The DGS-1008P has a compact design, so that you can place it in any easily accessible location and have it stay out of your way. The power connector and ports are all located at the rear of the switch allowing you to tuck the cables away conveniently. The DGS-1008P does not use a fan, so the switch operates silently but effectively, letting you watch movies streamed off the Internet without distraction, or browse the Web in peace.

Example Configuration



DGS-1008P 8-Port Gigabit PoE Unmanaged Desktop Switch

Technical Specifications

General

Hardware Version	• D1	
Interface	• 8 x 10/100/1000BASE-T ports	• PoE: ports 1 to 4
Standards	<ul style="list-style-type: none"> • IEEE 802.3 10BASE-T Ethernet • IEEE 802.3u 100BASE-TX Fast Ethernet • IEEE 802.3ab 1000BASE-T Gigabit Ethernet 	<ul style="list-style-type: none"> • IEEE 802.3az Energy Efficient Ethernet (EEE) • ANSI/IEEE 802.3 NWay auto-negotiation • IEEE 802.3x Flow Control
Media Interface Exchange	• Auto-MDI/MDI-X adjustment on all ports	

Performance

Switching Fabric	• 16 Gbps	
Transmission Method	• Store-and-forward	
Data Transfer Rates	<ul style="list-style-type: none"> • Gigabit Ethernet <ul style="list-style-type: none"> • 2000 Mbps (full duplex) • Fast Ethernet <ul style="list-style-type: none"> • 100 Mbps (half duplex) • 200 Mbps (full duplex) 	<ul style="list-style-type: none"> • Ethernet <ul style="list-style-type: none"> • 10 Mbps (half duplex) • 20 Mbps (full duplex)
Packet Filtering / Forwarding Rates	• 11.90 Mpps	
MAC Address Table	• 4K entries per device	
Jumbo Frame Size	• 9,720 bytes	
RAM Buffer	• 512 Kb	

PoE

PoE Standards	• IEEE 802.3af	• IEEE 802.3at
PoE-Capable Ports	• Ports 1 to 4	
PoE Power Budget	• 68 W (30 W max per PoE port)	

Physical

Weight	• 0.59 kg	
Dimensions	• 190 mm x 120 mm x 38 mm	
DC Input	• External 54 V / 1.67 A power adapter	
Power Consumption	• 80.2 W maximum (PoE on)	• 0.26 W maximum (PoE off)
Heat Dissipation	• 41.602 BTU/hr	
Temperature	• Operating: 0 to 40 °C (32 to 104 °F)	• Storage: -40 to 70 °C (-40 to 158 °F)
Humidity	• Operating: 0% to 95% RH non-condensing	
MTBF	• 631,894 hours	
Safety	<ul style="list-style-type: none"> • cUL • BSMI 	• LVD
EMI/EMC	<ul style="list-style-type: none"> • CE Class B • BSMI • FCC Class B 	<ul style="list-style-type: none"> • VCCI Class B • RCM • KCC



For more information: www.dlink.com

D-Link European Headquarters. D-Link (Europe) Ltd., First Floor, Artemis Building, Odyssey Business Park, West End Road, South Ruislip HA4 6QE, United Kingdom. Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2019 D-Link Corporation. All rights reserved. E&OE.

Updated September 2019

D-Link[®]