



Datenblatt - Fiche technique - Data sheet

21.15.1992



ROLINE S/FTP-(PiMF-) Patchkabel Kat.6A Component Level, LSOH, gelb, 1,5 m

Cordon ROLINE S/FTP(PiMF) Cat.6A / 10 Gigabit, LSOH, Component Level,
jaune, 1,5 m

ROLINE S/FTP Patch Cord Cat.6A, Component Level, LSOH, yellow, 1.5 m

1

2

3

4

5

6

 $1.5m \pm 20mm$
 $-0mm$

PLUG A

PIN.8

PIN.1

PLUG B

PIN.1

PIN.8

length mark

roline S/FTP PATCH CABLE 26AWG 4PR ISO/IEC 11801 & EN50288 CAT.6A LSOH XXXXXX-X

(1)Wiring:T568B

Specification :

Material :

1. RJ45 Plug :

- 1-1. Housing : Polycarbonate,Transparent color
- 1-2. Contact material : Phosphor Bronze with 50-60 micro-inch Nickel plated
- 1-3. Contact finished : Min. 50 micro-inch Gold plated on surface contact area
- 1-4. Shield : Bronze with Nickel plated

2. SR : SR-V95 FOR S/FTP Boot with nose


3. Cable :

- 3-1. Jacket : LSOH
- 3-2. Conductor : 26 AWG stranded copper
- 3-3. Isolation : PE
- 3-4. Shield : Aluminum Foil Shielded for Each Pair, copper clad with steel braid

4. Cable structure : S/FTP, 4 twisted pair

5. Minimum Bending Radius: 50mm

item no.	Jacket Color	
21.15.1990	grey	RAL7035
21.15.1991	red	RAL3031
21.15.1992	yellow	RAL1021
21.15.1993	green	RAL6029
21.15.1994	blue	RAL5015
21.15.1995	black	RAL9011
21.15.1996	white	RAL9003

item no	21.15.1990	21.15.1991	21.15.1992	21.15.1993	21.15.1994
	21.15.1995	21.15.1996			
Desc	ROLINE Cat 6a S/FTP Patch Cord,LSOH.Component Level,1.5m				
"#": Matching DIM.	DRAWING	10.MAR.2016	byz		
"*": Important DIM.	CHECK	10.MAR.2016	Jane		
Others General DIM.	APPROVAL	10.MAR.2016	Jaimy		
GENERAL TOLERANCE OF DIMENSIONS		DATE	NAME		
	SCALE	1/1 (A4)	UNIT		
X.XXX ±0.005 X.XX ±0.05 X.X ±0.1			DRAWING NO.		
			DRAWING CLASSIFICATION		S
			SHEET		1 OF 1
					

No.	MODIFIED AREA	ORIGINAL	MODIFY	DATE	MODIFIER

1

2

0

3

4

10cm

5

6