



Datenblatt - Fiche technique - Data sheet

21.15.9903



ROLINE LWL-Kabel 50/125µm SC/SC, grau, 3m

ROLINE Câble patch FO 50/125µm SC/SC, gris, 3m

ROLINE Fibre Optic Jumper Cable 50/125µm SC/SC, grey, 3 m

1

2

3

4

5

6

A

A


B

B

C

C

D



Specification:

1. Connector Type : SC Multimode
2. Cable Type :
 - 2-1 Zipcord Cable, $\phi 3.0\text{mm}$, 50/125um Multimode.
 - 2-2 Calbe Jacket : Gray Color, PVC Material.
3. Shrink Tube
4. Length : xM(FT)

Performance:

- a. Insertion Loss : $< 0.5 \text{ dB}$
- b. Fiber Extention : $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
- c. $\phi 2.5\text{mm}$ Ferrule End-face Radius : $8 < R < 25\text{mm}$
- d. Apex Offset : $< 50\mu\text{m}$
- e. Increase in insertion loss after 500 mating : 0.2 dB Max
- f. Operating Temperature : -20°C to $+70^\circ\text{C}$
- g. Storage Temperature : -40°C to $+80^\circ\text{C}$

Remack#

21.15.9900	MultiMode, SC-SC, 50/125 um	0.5M
21.15.9901	MultiMode, SC-SC, 50/125 um	1M
21.15.9902	MultiMode, SC-SC, 50/125 um	2M
21.15.9903	MultiMode, SC-SC, 50/125 um	3M
21.15.9905	MultiMode, SC-SC, 50/125 um	5M
21.15.9910	MultiMode, SC-SC, 50/125 um	10M

GENERAL TOLERANCE OF DIMENSIONS X.XXX ± 0.005 X.XX ± 0.05 X.X ± 0.1	DRAWING	06.JAN.2011	Abby	Rotronic Co.,Ltd.		
	CHECK	06.JAN.2011	MAER			
	APPROVAL	06.JAN.2011	YTY			
	DATE		NAME	ITEM NO.: 21.15.XXXX 有吊卡		
SCALE		1/1 (A4)	UNIT	mm	DES.: SC to SC Duplex patch cord	
		DRAWING NO.		SFBJB022323xxxx06001(SA1)		
		DRAWING CLASSIFICATION		S	SHEET 1 OF 1	

1

2

0

3

4

10cm

5

6