

INTRODUCTION

The AW-GEU-080A-250 is an 8-port GbE unmanaged PoE switch capable of feeding 15.4/30/60W (per port) power to Power over Ethernet (PoE) devices. The switch is capable of a total of 240 Watts power budget.

PACKAGE CONTENTS


* 1x PoE switch	* 1x Quick Installation Guide
* 1x rack mount kit	* 1x power cord (type by the shipped-to area)

⚠ IMPORTANT:

1. Install the PoE switch in a ventilated and dry place, that is free electromagnetic source, vibration, moisture, and dust.
2. Make sure the ventilation openings on the switch are not blocked.
3. Use CAT5 or 6 UTP/STP cables.
4. AC input (100~240V/AC, 50~60Hz), for a max. consumption of 250W.

CONNECTION

Front Panel



Rear Panel



Voltage regulator

LED DEFINITIONS

ACT	Green ON	Ethernet port are connected and normal.
	Fast blinking	Data is being transmitted or received.
	Off	No connection.
10/100M	Yellow ON	Ethernet port speed is 100Mbps.
	Off	Ethernet port speed is 10Mbps.
1000M	Green ON	Ethernet port speed is 1000Mbps.
	Off	No connection.
PoE	Yellow ON	Port is linked to a powered device.
	OFF	No device is connected.

All specifications are subject to change without notice.
Copyright © 2016 VIVOTEK INC. All rights reserved.