



LOOC

1080P H.265 Active Deterrence Wi-Fi Camera

LOOC delivers 2MP live monitoring, it supports the latest H.265 compression which can save up to 50% bandwidth and storage. With IP65 certified, the camera can be used outdoors under different weather conditions. With built-in spotlight and 110dB security siren, LOOC actively keeps unwelcome visitors away from what you care before he enters your home.



1080P FHD Video See more than 720P



Active Deterrence

Scare away unwelcome visitors with built-in spotlight and 110dB security siren



H.265 Codec

Save more high-quality video in less space



Two-way Talk
Communicate with family and pets easily



PIR Detection

High quality passive IR detector for reducing false alarms



IP65

Weatherproof for outdoor conditions



Wi-Fi Connection
IEEE802.11b/g/n(2.4GHz)



Micro SD Card Slot Supports up to 128GB local storage



Cloud Service

Live video, storage, alarm alerts and more



Stay close with what you care

With Cloud service, you will have access to what you care as long as Internet is available. You can record daily or motion videos on Cloud and play back anytime anywhere.





Specifications

Camera

1/2.7" 2 Megapixel Progressive CMOS

2MP(1920 x 1080)

Night Vision: 10m(33ft) Distance

2.8mm Fixed Lens

Field of View: 111° (H), 58° (V), 133° (D)

Video & Audio

Video Compression: H.265/H.264

Up to 25/30fps Frame Rate

16x Digital Zoom

Built-in Mic & Speaker, 110dB Siren

Built-in Spotlight

Notice Management

Motion Detection PIR Detection Configurable Region

What's in the box

- 1x Camera
- 1x Quick Start Guide
- 1x Power Adapter
- -1x Bracket
- -5x Screw Packages
- -1 x Installation Position Map
- -1x Cable Clip Package
- -1x Pry Bar

Network

Wi-Fi:IEEE802.11b/g/n,100m Open Field Internal Dual Antennas, 2 x 2 MIMO ONVIF Profile S, CGI

Lechange App: iOS, Android

Auxiliary Interface

Micro SD Card Slot(up to 128GB) Reset/WPS Button

General

DC 5V2A Power Supply

Power Consumption: ≤6W

Working Environment:-20° C~+50° C, Less Than 95%RH

IP65 Weatherproof

Dimensions: $75 \times 84 \times 97.7$ mm (2.95 \times 3.3 \times 3.8inch)

Weight: 308g (0.68lb)

CE, FCC, UL

