



Datenblatt - Fiche technique - Data sheet




21.88.2180



ROLINE GOLD S/FTP-(PiMF-) Patchkabel Kat.6A, 0,5 m

Cordon ROLINE GOLD Cat.6A S/FTP (PiMF), 0,5 m

ROLINE GOLD S/FTP Patch Cord Cat.6A, 0.5 m



NOTE:

1. ELECTRICAL TEST:

- (1). 100% OPEN SHORT, MISS WIRE TEST
- (2). INSULATION RESISTANCE: DC 300V 10MΩ ;
- (3). CONDUCTOR RESISTANCE: 3Ω Max (More than 3m, add one ohm per meter) ;

2. Fluke channel link test:


TEST LIMIT: ISO11801 Channel Class Ea

3. PRINT WORD:

CAT. 6A S/FTP LSZH 500MHz ISO/IEC 11801 & EN 50173-1 & ANSI/TIA-568-C.2

4. ROHS2.0 & REACH COMPLIANT

P1	P2
1	1 WHITE
2	2 ORANGE
3	3 WHITE
6	6 GREEN
4	4 BLUE
5	5 WHITE
7	7 WHITE
8	8 BROWN
shell	braided shell



COLOUR: BLACK & GOLD					
ITEM NO.	LENGTH (L)		TOLERANCE (T)		
21.15.2180	0.5m		±15mm		
21.15.2181	1m		±30mm		
21.15.2182	2m		±60mm		
21.15.2183	3m		±90mm		
21.15.2185	5m		±150mm		
21.15.2186	7m		±210mm		
21.15.2187	10m		±300mm		
21.15.2188	15m		±450mm		
21.15.2189	20m		±600mm		
ITEM NO.	21.15.2180	21.15.2181	21.15.2182	21.15.2183	21.15.2185
	21.15.2186	21.15.2187	21.15.2188	21.15.2189	
DESC.	ROLINE GOLD SFTP CAT. 6A Patch Cord With BLACK & GOLD Cotton Braiding				

MATERIAL LIST

③	OVER MOLD	PVC 75A BLACK.	2	
②	CONNECTOR	RJ45 8P8C Shielded Plug, Pin Gold Plated 3u", Shell Gold Plating Transparence	2	
①	CABLE	S/FTP CAT. 6A 27AWG (7/0.13BC*1P+AL-FOIL)*4PAIRS+BRAID (5*16/0.12mmAL-MG) JACKET: LSZH OD: 6.0±0.2mm, BLACK & GOLD Cotton Braiding OD: 6.5±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QTY	REMARK
		NEW		2015-10-21
BY	CHK	REVISION RECORD MODIFICATION	DATE	REV.

SECOMP