


MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION
①	CABLE	UTP [24AWG(CCA 7*0.192±0.005mm) *1PR]4+PE CROSS +LSOH OD:6.0±0.3mm COLOR: White
②	RJ45 CONNECTOR	RJ45, 8P8C, TWO FORK GOLD PLATED CONTACTS
③	MOLDING PVC	MOLDING PVC 50P COLOR:White

Marking: UTP CAT6 NETWORKING CABLE LSOH 24AWG*4P ISO/IEC 11801 & EN 50288 & ANSI/TIA-568-C.2 IEC 60332-1 IEC 60332-3C

- 1)Jacket Color:White(RAL 9003)
- 2)Wiring:T568B
- 3)Bending radius:The minimum bending radius is 8 times of the cable diameter



Item No	Length(M)	Tolerance(mm)
21.99.1026	0.5	+20/-10
21.99.1036	1	+/-20
21.99.0256	1.5	+/-40
21.99.1046	2	+/-40
21.99.1056	3	+/-60
21.99.1066	5	+/-110
21.99.1076	7	+/-140
21.99.1086	10	+/-200

ELECTRONIC TEST:
A.OPEN/SHORT/INTERMITTENCE: 100%.

ITEM NO.	21.99.1026/21.99.1036/21.99.0256/21.99.1046/21.99.1056 21.99.1066/21.99.1076/21.99.1086
DESC	VALUE Cat. 6 UTP Patch Cord,White
REMARK:NO	CHA NO
DRAWN BY	WEIHAIVAN
APPROVED BY	MORGAN
DATE	2024.07.31

