

Datenblatt - Fiche technique - Data sheet **26.99.0100**



VALUE 19"-KVM-Konsole, 43 cm (17") TFT (16:9), VGA, USB+PS/2, Tastaturlayout UK

VALUE Console 19", 1 UH, 43 cm (17") TFT, VGA, USB et PS/2, UK

VALUE 19" LCD KVM Console, 43 cm (17") TFT, VGA, USB + PS/2, UK



Item no.: 26.99.0100

VALUE 19" KVM Console, 43cm, VGA, USB+PS/2, UK keyboard,

black color



Features:

- Control platform with LCD, mouse touch board, keyboard, single port KVM switch
- Compatible with PS/2 USB standard interface
- Support VGA, SVGA, SGA video input
- Accord with DDC, DDC2, DDC2B standard and VESA standard
- Support resolution 1920 * 1080 (max.)
- 1U height, suitable for 19" standard cabinet installation and metal structure
- 43cm LCD screen with high brightness, high clear and high resolution
- Control platform can be totally pulled out from the cabinet and the LCD screen can be turned on to 120 degrees
- Mouse touch board with two function button
- Ultra thin keyboard with keypad, UK layout
- Front panel with lock to prevent damage by accident
- Built-in power
- Automatic power on/off, when pulling control platform out from cabinet, the power turns off automatically, when pushing it into the cabinet, the power turns on automatically

Specification:

Computer Connection		1	
CPU Port Selection		Front panel buttons	
Console Connector	Keyboard	Disassembled standard 99-key keyboard	
	Mouse	Standard PS/2 touch pad; rear side with USB connector	
	Video	43 cm SXGA color TFT-LCD	



Cable Connector	Keyboard	1 x PS/2 female (purple), 1 x USB female		
	Mouse	1 x PS/2 female (green), 1 x USB female		
	Video	1 x HDB-15 male (blue)		
LED	Online	1 x red LED		
	Selected	1 x green LED		
LCD monitor		monitor	43 cm SXGA Color TFT-LCD	
		visible square	337.92(H)*270.336(V)mm	
		Resolution(max)	1920 x 1080 60Hz	
		Support Color	16.7M colors (RGB 6-bit +Hi-FRC)	
		White Luminance	250 (center, Typ)@ 60 mA	
		contrast	1000:1 (Typ)	
		backlight	LED	
		Pixel Pitch	0.264(per one triad)x0.264	
		LCD MTBF	50,000 hours	
		Input power	DC 12V	
Mouse		X/Y resolution	1000dots/inch 40x40/mm)	
		hardware connector	Standard PS/2 & USB	
		OS support	WIN95/98/98SE/ME/200/XP/VISTA/7/8/NT, UNIX, LINUX	
		Using life	>1,000,000 times	
Power		Power (AC)	100V-240V	
		Using life	MTBF>60,000 hours 25 °C	
Housing col	or	black		
Housing material		Metal		
Gross weight		21.35 KGS		
Dimensions		640*443*42mm		
Rack installation depth		600mm ~ 1200mm(adjustable)		
Operating/storage Temperature		0 ~ 50 /-20 ~ 60°C		
PC ports		1		