



Datenblatt - Fiche technique - Data sheet

26.99.0103



VALUE 19"-KVM-Konsole, 43 cm (17") TFT (16:9), VGA, USB+PS/2,
Tastaturlayout F

VALUE Console 19", 1 UH, 43 cm (17") TFT, VGA, USB et PS/2, F

VALUE 19" LCD KVM Console, 43 cm (17") TFT, VGA, USB + PS/2, French

Item no.: 26.99.0103

VALUE 19" KVM Console, 43cm, VGA, USB+PS/2, French keyboard, black color



Features:

- Control platform with LCD, mouse touch board, keyboard, single port KVM switch
- Compatible with PS/2 USB standard interface
- Support VGA, SVGA, SGA video input
- Accord with DDC, DDC2, DDC2B standard and VESA standard
- Support resolution 1920 * 1080 (max.)
- 1U height, suitable for 19" standard cabinet installation and metal structure
- 43cm LCD screen with high brightness, high clear and high resolution
- Control platform can be totally pulled out from the cabinet and the LCD screen can be turned on to 120 degrees
- Mouse touch board with two function button
- Ultra thin keyboard with keypad, French layout
- Front panel with lock to prevent damage by accident
- Built-in power
- Automatic power on/off, when pulling control platform out from cabinet, the power turns off automatically, when pushing it into the cabinet, the power turns on automatically

Specification:

Computer Connection		1
CPU Port Selection		Front panel buttons
Console Connector	Keyboard	Disassembled standard 99-key keyboard
	Mouse	Standard PS/2 touch pad; rear side with USB connector
	Video	43 cm SXGA color TFT-LCD

Cable Connector	Keyboard	1 x PS/2 female (purple), 1 x USB female	
	Mouse	1 x PS/2 female (green) , 1 x USB female	
	Video	1 x HDB-15 male (blue)	
LED	Online	1 x red LED	
	Selected	1 x green LED	
LCD monitor		monitor	43 cm SXGA Color TFT-LCD
		visible square	337.92(H)*270.336(V)mm
		Resolution(max)	1920 x 1080 60Hz
		Support Color	16.7M colors (RGB 6-bit +Hi-FRC)
		White Luminance	250 (center, Typ)@ 60 mA
		contrast	1000:1 (Typ)
		backlight	LED
		Pixel Pitch	0.264(per one triad)x0.264
		LCD MTBF	50,000 hours
		Input power	DC 12V
Mouse		X/Y resolution	1000dots/inch 40x40/mm)
		hardware connector	Standard PS/2 & USB
		OS support	WIN95/98/98SE/ME/200/XP/VISTA/7/8/NT, UNIX, LINUX
		Using life	>1,000,000 times
Power		Power (AC)	100V-240V
		Using life	MTBF>60,000 hours 25 °C
Housing color		black	
Housing material		Metal	
Gross weight		21.35 KGS	
Dimensions		640*443*42mm	
Rack installation depth		600mm ~ 1200mm(adjustable)	
Operating/storage Temperature		0 ~ 50 /-20 ~ 60°C	
PC ports		1	