

WEIGHT	CUSTOMER NO:	REMARK
		SECOMP

NOTES:

- 1. PIN ASSIGNMENT SEE TO WIRE LIST.
- 2. ELECTRICAL TEST CONDITION:
 - (a). 100% OPEN, SHORT & MISWIRE TEST,
 - (b). INSULATOR RESISTANCE: 10 Mohm MIN. DC 300V 0.01sec.
 - (c). CONTACT RESISTANCE: 3ohm MAX.

PIN ASSIGNMENT

P1		P2
1	8	1
2		2
3		3
6	8	6
4		4
5	8	5
7	8	7
8		8
S		

4	OVERMOLD BLACK PVC 45P MA-001.	
3	TERMINAL BLOCK GREEN 8PIN.	
2	8P8C PLUG WITH NICKLE PLATED SHELL.	
1	UTP CAT5E 24AWG*4P+AE OD:6.0MM L:300mm BLACK PVC JACKET.	
NO.	Description	P/N

A		FIRST EDITION	BAO	2024/07/09
REV.	ECR	DESCRIPTION	C.N.	DATE
SECOMP				
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1.0°		TITLE RJ45 M- Push-Teminal Block Connector Cable Adapter		
DIMENSIONS		TOLERANCE		CHKD.
0.00 TO 30.00mm		±0.10mm		CONF.
30.01 TO 80.00mm		±0.13mm		DR.
80.01 TO 150.00mm		±0.15mm		BAO
150.01mm		±0.20mm		MODEL NO:
MATERIAL		MATERIAL		12.02.1171
FINISH		FINISH		SCALE
				SHEET 1 / 1
				UNIT MM
				SIZE A4
				REV. A