



**MATERIAL LIST:**

⑪	Dust Cover	PE Color:Natural color	1	
⑩	MOLDING	PVC Color:BLACK	1	
⑨	Housing	ABS Color:BLACK	1	
⑧	SR	PCV COLOR: Bleak	1	
⑦	PCBA	IC:CH7213+PS8348+PS176+TV3DV642+RTD2166	1	
⑥	DP	DP FEMALE, BLACK INSULATION, THE PIN GOLD PLATED, THE SHELL NICKEL PLATED	1	
⑤	DVI	DVI24+5 FEMALE, WHITE INSULATION, THE PIN GOLD PLATED, THE SHELL NICKEL PLATED	1	
④	VGA	VGA FEMALE, COLD GRAY INSULATION, THE PIN GOLD PLATED, THE SHELL NICKEL PLATED	1	
③	HDMI	HDMI A FEMALE, BLACK INSULATION, THE PIN GOLD PLATED, THE SHELL NICKEL PLATED	1	
②	USB C TYPE	USB Type C/M, BLACK PBT INSULATION, THE PIN GOLD PLATING, THE SHELL NICKEL PLATING	1	
①	CABLE	34AWG (TC*1P+D+AL+HM)*5C+34AWG (TC*4C)+34AWG (TC*2C)+AB OD=4.2±0.2mm PVC COLOR:BLACK	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK

**NOTE:**

- 100% HDTV 4K TEST
- Type C male input, DP/HDMI/DVI/SVGA Output; (Only supports a single port output)
- DP1.2 Female output: 3840\*2160@60Hz
- HDMI2.0a Female output: 3840\*2160@60Hz
- DVI24+5 Female output: 3840\*2160@30Hz
- SVGA Female output: 1920\*1080@60Hz
- Note book: Mac book 2015, Mac book pro 2017, Dell xps13 xps15 Etc.
- Support Windows10, MAC OS10.12 System
- Operating Temperature: 0°C ~ 45°C
- Storage Temperature: -20°C ~ 70°C
- RoHS (EU 2015/863) and REACH Compliant

ITEM NO.	12.99.3231
Color	Black
DESC.	VALUE USB Type C to VGA/DVI/HDMI/DP Converter

		NEW	2019.03.21	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

**SECOMP**