

Datenblatt - Fiche technique - Data sheet **14.99.3431**



VALUE VGA-Verlängerung via TP, max. 80m

VALUE Prolongateur VGA via TP, 80 m

VALUE VGA Extender over Twisted Pair, 80 m

VGA EXTENDER





(14.99.3431)

USER MANUAL

Package Contents-

- VGA-L80 Local Unit
- VGA-R80 Remote Unit
- 1 user manual
- 1 power adapter DC 12V/600mA
- 1 1.2M cable (HD-15 Male to Male)

Anything missed, please contact with your vendor.

Features

- The extension of VGA signal is up to 80 meter away by using the VGA Extender and one CAT.5 cable.
- Equalization length is adjustable.
- VGA signal gain is adjustable.
- Support "power over cable" technique, only one unit (Local or Remote) need to connect to power.
- Both "Local" and "Remote" can act as the PSE (power source equipment).

Specifications

Function	VGA-L80	VGA-R80
VGA In/Out Connector	HD-15 Female x 1	
RJ-45 Connector	1	
Max. Resolution	1280x1024 60Hz	
Cable Distance	80 m (Max.)
Power Adapter (Min.)	DC 12V 600mA	
Housing	Metal	
Weight	135g	140g
Dimensions (LxWxH)	92x34x22 mm	

LOCAL FRONT VIEW



- 1. Power jack
- 2. Power LED

V1.0

3. CAT.5 (RJ-45 Connector)

LOCAL REAR VIEW



1. VGA In (HD-15 Female Connector)

-1-

REMOTE FRONT VIEW



- 1. Power jack
- 2. Power LED
- 3. CAT.5 (RJ-45 Connector)

REMOTE REAR VIEW



1. VGA Out (HD-15 Female Connector)

REMOTE BOTTOM VIEW



- 1. EQ Equalization length adjust (Adjust it and weak characters be sharp)
- 2. GAIN Adjust brightness

Installation

- 1. Turn off the PC.
- 2. Connect 14.99.3431 Local Unit HD-15 female connector with HD-15 male to male cable from PC.
- 3. Connect the 14.99.3431 Local and Remote Unit with CAT.5 cable.
- 4. Connect 14.99.3431 Remote Unit HD-15 female connector with HD-15 male to male cable from monitor.
- 5. Turn on the monitor and PC.

P.S. For better video quality, we suggest connect power to "Remote" unit. When connect power to "Local" unit, due to the characteristic and quality, the transmission distances may decreases.

-2-


Distances and Resolutions for CAT.5/5E and CAT.6 cables

CAT.5/5E	50M	2048x1536
	80M	1280x1024
		1024x768
		800x600
CAT.6	30M	1920x1440
	50M	1280x1024
	80M	800x600

PS. We suggest to use CAT.5 cable because of the performance is better than others.

Wiring Information & Coding

Conductor	RJ45 Pin	Color Code for	
Identification	Assignment	Conductor	
Pair 1	5	White-Blue	
	4	Blue	
Pair 2	1	White-Orange	
	2	Orange	
Pair 3	3	White-Green	
	6	Green	
Pair 4	7	White-Brown	
	8	Brown	



Trademarks:

All the companies, brand names, and product names referred to this manual are the trademarks or registered trademarks belonging to their respective companies.