

Datenblatt Art. 927.053

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

KAPSA S

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Zuleitung	0,2m H05VV-F 3G1,5mm ²	Supply cable	0,2m H05VV-F 3G1,5mm ²
Farbe Zuleitung	Schwarz	Colour supply cable	Black
Stecker	Installationsstecker	Plug	Building installation plug
Stromausgang		Power output	
Steckdosen 3x CEE 7/5 (Type E) 2-polig mit Schutzkontakt Mit erhöhtem Berührungsschutz Schwarz, ähnlich RAL 9005, 35° 16A / 250V~, IP20		Socket outlets 3x CEE 7/5 (Type E) 2-pole with earthing contact With shutter Black, similar to RAL 9005, 35° 16A / 250V~, IP20	
Weitere Produkteigenschaften		Further product attributes	
Abmessungen ca.	204x50x70mm	Dimensions	204x50x70mm
Tischplattenstärke	10-40mm	Tabletop thickness	10-40mm
Einbautiefe	45mm	Mounting depth	45mm
Plattform	Standard (kHE)	Platform	Standard (kHE)
Material Gehäuse: Aluminium, eloxiert Abdeckung: PA6 850°C, schwarz ähnlich RAL 9005		Material Housing Aluminium, anodised Cover: PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang 1x Steckdosenleiste KAPSA Small		Scope of delivery 1x Power strip KAPSA Small	
Im Karton		In carton	
Optionales Zubehör Deckel KAPSA S		Optional accessories Lid KAPSA S	

Umgebungsbedingungen		Environmental conditions	
Umgebungstemperatur bei Montage und Nutzung	5°C – 35°C	Surrounding temperature during mounting and use	5°C – 35°C
Vor direkter Sonneneinstrahlung schützen.		Protect from direct sunlight.	
Umgebungstemperatur bei Transport und Lagerung	-25°C - 60°C	Surrounding temperature during transport and storage	-25°C - 60°C
Relative Luftfeuchtigkeit (nicht kondensierend)	5 – 95%	Relative humidity (non-condensing)	5 – 95%
Schutzart	IP20	Protection type	IP20
Konformität / Approbation		Conformity / Approval	
Bauart geprüft	NF C 61-314	Type approved	NF C 61-314