



Elevator 1xUK 90° und USB Doppelcharger	Elevator 1xUK 90° and USB double charger
Steckdosen: <ul style="list-style-type: none"> nach BS 1363 2-polig mit Schutzkontakt 13A/3680W, AC250V, IP20, mit erhöhtem Berührungsschutz Schwarz, um 90° gedreht, mit Sicherung 5A 	Sockets: <ul style="list-style-type: none"> According to BS 1363 2-pole with earthing contact 13A/3680W, AC250V, IP20, with shutter Black, set at 90°, fused with 5A
Custom Modul: <ul style="list-style-type: none"> 1xUSB Doppelcharger 5V / 3,1A 	Custom Module: <ul style="list-style-type: none"> 1xUSB Double Charger 5V / 3,1A
Anschluss: <ul style="list-style-type: none"> 2,0m H05VV-F 3G1,5mm² schwarz mit UK Stecker 13A montiert 	Connection: <ul style="list-style-type: none"> 2,0m H05VV-F 3G1,5mm² black with UK plug 13A mounted
Befestigung: <ul style="list-style-type: none"> Tischausschnitt Ø80mm Für Plattenstärken von 16mm bis 60mm Einbautiefe 135mm Fixierung über Schraubring 	Mounting: <ul style="list-style-type: none"> Table cut-out Ø80 For tabletop thicknesses from 16mm to 60mm Mounting depth 135mm Mounting via ring nut
Material: <ul style="list-style-type: none"> Kunststoff: Schwarz, PA6 GF 30 V1, Glühdraht-Prüfung bis 850°C Profil: Aluminium, eloxiert und poliert, „Edelstahl-Look“, Strangguss Blenden: Aluminium, eloxiert und gebürstet 	Material: <ul style="list-style-type: none"> Plastic: Black, PA6 GF 30 V1, glow wire resistant up to 850°C Housing: Aluminum, anodised and polished "stainless steel look", continuous casting Cover: Aluminium, anodised and stamped
Abmessungen in mm: <ul style="list-style-type: none"> Siehe Zeichnung 	Measurements in mm: <ul style="list-style-type: none"> According to drawing
Lieferform: <ul style="list-style-type: none"> In Karton verpackt 	Packaging: <ul style="list-style-type: none"> In carton
Lieferumfang: <ul style="list-style-type: none"> 1x Elevator Steckdoseneinheit 1x Montageanleitung 	Extent of delivery: <ul style="list-style-type: none"> 1x Elevator power strip 1x Mounting instruction