

Datenblatt Art. 902.0853

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

DESK Steckdosenleiste / DESK power strip

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	13A / 250V~	Rated current / rated voltage	13A / 250V~
Frequenz	50 / 60Hz	Frequency	50 / 60Hz
Netzanschluss		Power supply	
Stecker	Installationssteckverbinder	Plug	Building installation connector
Kupplung	Installationssteckverbinder	Coupling	Building installation connector
	2-polig mit Schutzkontakt		2-pole with earthing contact
	Schwarz, ähnlich RAL 9005		Black, similar to RAL 9005
	20A / 250V~, IP20		20A / 250V~, IP20
Stromausgang		Power output	
Steckdosen	Socket outlets	Socket outlets	Socket outlets
2x UK BS 1363 (Type G)	2x UK BS 1363 (Type G)	2x UK BS 1363 (Type G)	2x UK BS 1363 (Type G)
2-polig mit Schutzkontakt	2-pole with earthing contact	2-pole with earthing contact	2-pole with earthing contact
Mit erhöhtem Berührungsschutz	With shutter	With shutter	With shutter
Schwarz, ähnlich RAL 9005, 45°	Black, similar to RAL 9005, 45°	Black, similar to RAL 9005, 45°	Black, similar to RAL 9005, 45°
Integrierte Sicherung 3,15 A	Integrated Fuse 3,15A	Integrated Fuse 3,15A	Integrated Fuse 3,15A
13A / 250V~, IP20	13A / 250V~, IP20	13A / 250V~, IP20	13A / 250V~, IP20
Funktionsmodule		Function modules	
1x USB-C Charger 60W (85mm)	1x USB-C Charger 60W (85mm)	1x USB-C Charger 60W (85mm)	1x USB-C Charger 60W (85mm)
Ausgangsspannung / Ausgangsstrom /	DC5.0V 3.0A 15.0W	Output voltage / Output current /	DC5.0V 3.0A 15.0W
Ausgangsleistung C-port	DC9.0V 3.0A 27.0W	Output power C-port	DC9.0V 3.0A 27.0W
	DC15.0V 3.0A 45.0W		DC15.0V 3.0A 45.0W
	DC20V 3.0A 60.0W		DC20V 3.0A 60.0W
Durchschnittseffizienz	Average active efficiency	Average active efficiency	Average active efficiency
C port DC5.0V 3.0A 15.0W	84.6 %	C port DC5.0V 3.0A 15.0W	84.6 %
C port DC9.0V 3.0A 27.0W	87.9 %	C port DC9.0V 3.0A 27.0W	87.9 %
C port DC15.0V 3.0A 45.0W	90.0 %	C port DC15.0V 3.0A 45.0W	90.0 %
C port DC20V 3.0A 60.0W	90.3 %	C port DC20V 3.0A 60.0W	90.3 %
Effizienz bei niedriger Last 10%	Efficiency at low load (10%)	Efficiency at low load (10%)	Efficiency at low load (10%)
C port DC5.0V 3.0A 15.0W	81.0 %	C port DC5.0V 3.0A 15.0W	81.0 %
C port DC9.0V 3.0A 27.0W	83.0 %	C port DC9.0V 3.0A 27.0W	83.0 %

C port DC15.0V 3.0A 45.0W	84.7 %	C port DC15.0V 3.0A 45.0W	84.7 %
C port DC20V 3.0A 60.0W	84.0 %	C port DC20V 3.0A 60.0W	84.0 %
Leistungsaufnahme bei Nulllast	0.08W	No-load power consumption	0.08W
Ladestandard		Charging standards	
Power Delivery	USB 3.1 PD	Power Delivery	USB 3.1 PD

Weitere Produkteigenschaften

Material

Gehäuse:

Aluminium, eloxiert

Abdeckung und Endkappen:

PA6 GF30 850°C

schwarz ähnlich RAL 9005

Lieferumfang

1x DESK Steckdosenleiste

Im Karton

Further product attributes

Material

Housing:

Aluminium, anodised

Cover and endcaps:

PA6 GF30 850°C

black similar to RAL 9005

Scope of delivery

1x DESK Power strip

in carton

Umgebungsbedingungen

Umgebungstemperatur bei Montage und Nutzung 5°C - 35°C

Umgebungstemperatur bei Transport und Lagerung -20°C - 60°C

Relative Luftfeuchtigkeit (nicht kondensierend) 10 - 90%

Luftdruck 80 - 108kPa

Schutzart IP20

Environmental conditions

Surrounding temperature during mounting and use 5°C - 35°C

Surrounding temperature during transport and storage -20°C - 60°C

Relative humidity (non-condensing) 10 - 90%

Air pressure 80 - 108kPa

Protection type IP20

Konformität

Angewandte Normen

IEC 62368-1 (USB-Charger)
EN 62368-1 (USB-Charger)

Applied standards

IEC 62368-1 (USB-Charger)
EN 62368-1 (USB-Charger)

