

Datenblatt Art. 902.801

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

DESK2 Steckdosenleiste / DESK2 power strips

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50Hz	Frequency	50Hz
Netzanschluss		Power supply	
Zuleitung	0,2m H05VV-F 3G1,5mm ²	Supply cable	0,2m H05VV-F 3G1,5mm ²
Farbe Zuleitung	Schwarz	Colour supply cable	Black
Stecker	Installationsstecker	Plug	Building installation plug
Stromausgang		Power output	
Steckdosen 2x CEE 7/3 (Type F) 2-polig mit Schutzkontakt Mit erhöhtem Berührungsschutz Schwarz, ähnlich RAL 9005, 35° 16A / 250V~, IP20		Socket outlets 2x CEE 7/3 (Type F) 2-pole with earthing contact With shutter Black, similar to RAL 9005, 35° 16A / 250V~, IP20	
Funktionsmodule		Function modules	
Custom Module 1x Custom Module leer		Custom Modules 1x Custom Module empty	
USB-A Charger 15W (42,5mm)		USB-A Charger 15W (42,5mm)	
Doppelcharger	DC 5 V 3,1 A	Double charger	DC 5 V 3,1 A
USB-Spezifikation	USB 3.0	USB standard	USB 3.0
iotspot Modul Tisch und Raumbuchungssystem LED Farben mit 7 RGB LEDs Funkfrequenzbänder und max. Sendeleistung LTE-M (Cat M1) 1.4 MHZ		iotspot Module Table and room booking system LED colours with 7 RGB LEDs Radio frequency bands and max. transmission power LTE-M (Cat M1) 1.4 MHZ	
	grün, rot, blau, orange		green, red, blue, orange
	23 dBm		23 dBm
EGSM 900 MHz	33 dBm	EGSM 900 MHz	33 dBm
EGSM 1.800 MHz	30 dBm	EGSM 1.800 MHz	30 dBm
Bluetooth 2.4 GHz	4 dBm	Bluetooth 2.4 GHz	4 dBm
NFC 13.56 MHz	Passive	NFC 13.56 MHz	Passive

Material
PA6 GF30 850°C,
schwarz ähnlich RAL
9005

Material
PA6 GF30 850°C,
black similar to RAL
9005

Weitere Produkteigenschaften

Further product attributes

Plattform Standard (kHE)

Plattform Standard (kHE)

Material
Gehäuse:
Aluminium, lackiert in schwarz ähnlich RAL
9005

Material
Housing:
Aluminium, painted in black similar to RAL
9005

Abdeckung:
PA6 GF30 850°C, schwarz ähnlich RAL
9005

Cover:
PA6 GF30 850°C, black similar to RAL 9005

Lieferumfang
1x DESK2 Steckdosenleiste
inkl. Haltewinkel

Scope of delivery
1x DESK2 power strip
incl. Mounting brackets

Im Karton

In carton

Umgebungsbedingungen

Environmental conditions

Maximale Höhe 0 - 2000m
Umgebungstemperatur bei Montage und Nutzung 5°C – 35°C
Vor direkter Sonneneinstrahlung schützen.
Umgebungstemperatur bei Transport und Lagerung -25°C - 60°C
Relative Luftfeuchtigkeit (nicht kondensierend) 5 – 95%
Luftdruck 80-108 kPa
Schutzart IP20

Maximum height 0 - 2000m
Surrounding temperature during mounting and use 5°C – 35°C
Protect from direct sunlight.
Surrounding temperature during transport and storage -25°C - 60°C
Relative humidity (non-condensing) 5 – 95%
Air pressure 80-108 kPa
Protection type IP20

Konformität

Conformity /

Angewandte Normen
IEC 62368-1 (USB-Charger)
EN 62368-1 (USB-Charger)

Applied standards
IEC 62368-1 (USB-Charger)
EN 62368-1 (USB-Charger)