

Datenblatt Art. 706.008

Data sheet | Fiche technique | Scheda tecnica | Fişa tehnică

CYCLE Base Steckdosenleiste / CYCLE Base power strip

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung Frequenz	10 A / 230 V 50 Hz	Rated current / rated voltage Frequency	10 A / 230 V 50 Hz
Netzanschluss		Power supply	
Zuleitung Farbe Zuleitung	0,2 m H05Z1Z1 3G1,5 mm ² Schwarz	Supply cable Colour supply cable	0,2 m H05Z1Z1 3G1,5 mm ² Black
Stecker	Installationsstecker	Plug	Building installation plug
Stromausgang		Power output	
Steckdosen 4x SEV 1011 T13 (Type J) 2-polig mit Schutzkontakt Schwarz, ähnlich RAL 9005, 0° 10 A / 250 V~, IP20		Socket outlets 4x SEV 1011 T13 (Type J) 2-pole with earthing contact Black, similar to RAL 9005, 0° 10 A / 250 V~, IP20	
Funktionsmodule		Function modules	
Schalter Blau beleuchtet USB A&C Charger 22 W (42,5 mm) Ausgangsspannung / Ausgangsstrom / Ausgangsleistung C-port		Switch Blue illuminated USB A&C Charger 22 W (42,5 mm) Output voltage / Output current / Output power C-port	
	DC 5.0 V 3.0 A 15.0 W DC 9.0 V 2.3 A 20.7 W DC 15.0 V 1.4 A 21 W DC 20.0 V 1.1 A 22 W		DC 5.0 V 3.0 A 15.0 W DC 9.0 V 2.3 A 20.7 W DC 15.0 V 1.4 A 21 W DC 20.0 V 1.1 A 22 W
Ausgangsspannung / Ausgangsstrom / Ausgangsleistung Q-port	DC 5.0 V 3.0 A 15 W DC 9.0 V 2.0 A 18.0 W DC 12.0 V 1.5 A 18.0 W	Output voltage / Output current / Output power Q-port	DC 5.0 V 3.0 A 15 W DC 9.0 V 2.0 A 18.0 W DC 12.0 V 1.5 A 18.0 W
Ausgangsspannung / Ausgangsstrom / Ausgangsleistung C port + Q port (beide Ausgänge)	DC 5.0 V 3.5 A 17.5 W	Output voltage / Output current / Output power C port + Q port (both output)	DC 5.0 V 3.5 A 17.5 W
Durchschnittseffizienz		Average active efficiency	
C port DC 5.0 V 3.0 A 15.0 W	83.0 %	C port DC 5.0 V 3.0 A 15.0 W	83.0 %
C port DC 9.0 V 2.3 A 20.7 W	86.4 %	C port DC 9.0 V 2.3 A 20.7 W	86.4 %
C port DC 15.0 V 1.4 A 21.0 W	86.9 %	C port DC 15.0 V 1.4 A 21.0 W	86.9 %
C port DC 20.0 V 1.1 A 22 W	86.5 %	C port DC 20.0 V 1.1 A 22 W	86.5 %
Q-port DC 5.0 V 3.0 A 15.0 W	83.1 %	Q-port DC 5.0 V 3.0 A 15.0 W	83.1 %

Q-port DC 9.0 V 2.0 A 18.0 W 85.4 %
 Q-port DC 12.0 V 1.5 A 18.0 W 86.0 %
 C port + Q port DC 5.0 V 3.5 A 17.5 W 83.9 %

Effizienz bei niedriger Last (10 %)
 C port DC 5.0 V 3.0 A 15.0 W 80.7 %
 C port DC 9.0 V 2.3 A 20.7 W 80.3 %
 C port DC 15.0 V 1.4 A 21.0 W 77.0 %
 C port DC 20.0 V 1.1 A 22 W 73.5 %
 Q port DC 5.0 V 3.0 A 15.0 W 80.8 %
 Q port DC 9.0 V 2.0 A 18.0 W 83.6 %
 Q port DC 12.0 V 1.5 A 18.0 W 82.8 %
 C port + Q port DC 5.0 V 3.5 A 17.5 W 82.8 %

Leistungsaufnahme bei Nulllast 0.09 W

Ladestandard
 Power Delivery USB 3.1 PD

Q-port DC 9.0 V 2.0 A 18.0 W 85.4 %
 Q-port DC 12.0 V 1.5 A 18.0 W 86.0 %
 C port + Q port DC 5.0 V 3.5 A 17.5 W 83.9 %

Efficiency at low load (10 %)
 C port DC 5.0 V 3.0 A 15.0 W 80.7 %
 C port DC 9.0 V 2.3 A 20.7 W 80.3 %
 C port DC 15.0 V 1.4 A 21.0 W 77.0 %
 C port DC 20.0 V 1.1 A 22 W 73.5 %
 Q port DC 5.0 V 3.0 A 15.0 W 80.8 %
 Q port DC 9.0 V 2.0 A 18.0 W 83.6 %
 Q port DC 12.0 V 1.5 A 18.0 W 82.8 %
 C port + Q port DC 5.0 V 3.5 A 17.5 W 82.8 %

No-load power consumption 0.09 W

Charging standards
 Power Delivery USB 3.1 PD

Schutzeinrichtungen

Thermische Sicherungen

Bemessungsspannung 230 V~
 Bemessungsstrom 10 A
 Typ Bimetallsicherung (rückstellbar)

Protective devices

Fuses

Rated voltage 230 V~
 Rated current 10 A
 Type Bimetal fuse (resetable)

Weitere Produkteigenschaften

Plattform Standard (kHE)

Material

Gehäuse:
 Aluminium, eloxiert

Abdeckung:

AKROMID® NEXT 5.6 3 GF 30 FR,
 schwarz

Lieferumfang

1x CYCLE Base Steckdosenleiste

Im Karton

Further product attributes

Plattform Standard (kHE)

Material

Housing:
 Aluminium, anodised

Cover:

AKROMID® NEXT 5.6 3 GF 30 FR, black

Scope of delivery

1x CYCLE Base power strip

In carton

Umgebungsbedingungen

Maximale Höhe 2000 m
Umgebungstemperatur bei Montage und Nutzung 5 °C – 35 °C
Vor direkter Sonneneinstrahlung schützen.
Umgebungstemperatur bei Transport und Lagerung -20 °C - 60 °C
Relative Luftfeuchtigkeit (nicht kondensierend) 10 % – 90 %
Schutzart IP20

Environmental conditions

Maximum height 2000 m
Surrounding temperature during mounting and use 5 °C – 35 °C
Protect from direct sunlight.
Surrounding temperature during transport and storage -20 °C - 60 °C
Relative humidity (non-condensing) 10 % – 90 %
Protection type IP20

Konformität	Conformity
-------------	------------

Angewandte Normen	IEC 62368-1 (USB-Charger) EN 62368-1 (USB-Charger)	Applied standards	IEC 62368-1 (USB-Charger) EN 62368-1 (USB-Charger)
--------------------------	---	--------------------------	---