

## Datenblatt Art.

**708.010**

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

### CYCLE Desk Steckdosenleiste / CYCLE Desk power strip

| Elektrische Kenngrößen                                                               |                                                                                                | Electrical parameters                                                        |                                                                                                |
|--------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| <b>Nennstrom / Bemessungsspannung</b>                                                | 10 A / 230 V                                                                                   | <b>Rated current / rated voltage</b>                                         | 10 A / 230 V                                                                                   |
| <b>Frequenz</b>                                                                      | 50 Hz                                                                                          | <b>Frequency</b>                                                             | 50 Hz                                                                                          |
| Netzanschluss                                                                        |                                                                                                | Power supply                                                                 |                                                                                                |
| <b>Zuleitung</b>                                                                     | <b>0,2 m   H05Z1Z1  </b>                                                                       | <b>Supply cable</b>                                                          | <b>0,2 m   H05Z1Z1  </b>                                                                       |
| Farbe Zuleitung                                                                      | 3G1,5 mm <sup>2</sup><br>Schwarz                                                               | Colour supply cable                                                          | 3G1,5 mm <sup>2</sup><br>Black                                                                 |
| <b>Stecker</b>                                                                       | <b>Installationsstecker</b>                                                                    | <b>Plug</b>                                                                  | <b>Building installation plug</b>                                                              |
| Stromausgang                                                                         |                                                                                                | Power output                                                                 |                                                                                                |
| <b>Steckdosen</b>                                                                    |                                                                                                | <b>Socket outlets</b>                                                        |                                                                                                |
| <b>2x SEV 1011 T13 (Type J)</b>                                                      |                                                                                                | <b>2x SEV 1011 T13 (Type J)</b>                                              |                                                                                                |
| 2-polig mit Schutzkontakt                                                            |                                                                                                | 2-pole with earthing contact                                                 |                                                                                                |
| Schwarz, ähnlich RAL 9005, 0°                                                        |                                                                                                | Black, similar to RAL 9005, 0°                                               |                                                                                                |
| 10 A / 250 V~, IP20                                                                  |                                                                                                | 10 A / 250 V~, IP20                                                          |                                                                                                |
| Funktionsmodule                                                                      |                                                                                                | Function modules                                                             |                                                                                                |
| <b>Schalter</b>                                                                      |                                                                                                | <b>Switch</b>                                                                |                                                                                                |
| Blau beleuchtet                                                                      |                                                                                                | Blue illuminated                                                             |                                                                                                |
| <b>USB A&amp;C Charger 22 W (42,5 mm)</b>                                            |                                                                                                | <b>USB A&amp;C Charger 22 W (42,5 mm)</b>                                    |                                                                                                |
| Ausgangsspannung / Ausgangsstrom / Ausgangsleistung C-port                           | DC 5.0 V 3.0 A 15.0 W<br>DC 9.0 V 2.3 A 20.7 W<br>DC 15.0 V 1.4 A 21 W<br>DC 20.0 V 1.1 A 22 W | Output voltage / Output current / Output power C-port                        | DC 5.0 V 3.0 A 15.0 W<br>DC 9.0 V 2.3 A 20.7 W<br>DC 15.0 V 1.4 A 21 W<br>DC 20.0 V 1.1 A 22 W |
| Ausgangsspannung / Ausgangsstrom / Ausgangsleistung Q-port                           | DC 5.0 V 3.0 A 15 W<br>DC 9.0 V 2.0 A 18.0 W<br>DC 12.0 V 1.5 A 18.0 W                         | Output voltage / Output current / Output power Q-port                        | DC 5.0 V 3.0 A 15 W<br>DC 9.0 V 2.0 A 18.0 W<br>DC 12.0 V 1.5 A 18.0 W                         |
| Ausgangsspannung / Ausgangsstrom / Ausgangsleistung C port + Q port (beide Ausgänge) | DC 5.0 V 3.5 A 17.5 W                                                                          | Output voltage / Output current / Output power C port + Q port (both output) | DC 5.0 V 3.5 A 17.5 W                                                                          |
| Durchschnittseffizienz                                                               |                                                                                                | Average active efficiency                                                    |                                                                                                |
| C port DC 5.0 V 3.0 A 15.0 W                                                         | 83.0 %                                                                                         | C port DC 5.0 V 3.0 A 15.0 W                                                 | 83.0 %                                                                                         |
| C port DC 9.0 V 2.3 A 20.7 W                                                         | 86.4 %                                                                                         | C port DC 9.0 V 2.3 A 20.7 W                                                 | 86.4 %                                                                                         |

|                                       |        |
|---------------------------------------|--------|
| C port DC 15.0 V 1.4 A 21.0 W         | 86.9 % |
| C port DC 20.0 V 1.1 A 22 W           | 86.5 % |
| Q-port DC 5.0 V 3.0 A 15.0 W          | 83.1 % |
| Q-port DC 9.0 V 2.0 A 18.0 W          | 85.4 % |
| Q-port DC 12.0 V 1.5 A 18.0 W         | 86.0 % |
| C port + Q port DC 5.0 V 3.5 A 17.5 W | 83.9 % |

|                                       |        |
|---------------------------------------|--------|
| Effizienz bei niedriger Last (10 %)   |        |
| C port DC 5.0 V 3.0 A 15.0 W          | 80.7 % |
| C port DC 9.0 V 2.3 A 20.7 W          | 80.3 % |
| C port DC 15.0 V 1.4 A 21.0 W         | 77.0 % |
| C port DC 20.0 V 1.1 A 22 W           | 73.5 % |
| Q port DC 5.0 V 3.0 A 15.0 W          | 80.8 % |
| Q port DC 9.0 V 2.0 A 18.0 W          | 83.6 % |
| Q port DC 12.0 V 1.5 A 18.0 W         | 82.8 % |
| C port + Q port DC 5.0 V 3.5 A 17.5 W | 82.8 % |

|                                |        |
|--------------------------------|--------|
| Leistungsaufnahme bei Nulllast | 0.09 W |
|--------------------------------|--------|

|                |            |
|----------------|------------|
| Ladestandard   |            |
| Power Delivery | USB 3.1 PD |

|                                       |        |
|---------------------------------------|--------|
| C port DC 15.0 V 1.4 A 21.0 W         | 86.9 % |
| C port DC 20.0 V 1.1 A 22 W           | 86.5 % |
| Q-port DC 5.0 V 3.0 A 15.0 W          | 83.1 % |
| Q-port DC 9.0 V 2.0 A 18.0 W          | 85.4 % |
| Q-port DC 12.0 V 1.5 A 18.0 W         | 86.0 % |
| C port + Q port DC 5.0 V 3.5 A 17.5 W | 83.9 % |

|                                       |        |
|---------------------------------------|--------|
| Efficiency at low load (10 %)         |        |
| C port DC 5.0 V 3.0 A 15.0 W          | 80.7 % |
| C port DC 9.0 V 2.3 A 20.7 W          | 80.3 % |
| C port DC 15.0 V 1.4 A 21.0 W         | 77.0 % |
| C port DC 20.0 V 1.1 A 22 W           | 73.5 % |
| Q port DC 5.0 V 3.0 A 15.0 W          | 80.8 % |
| Q port DC 9.0 V 2.0 A 18.0 W          | 83.6 % |
| Q port DC 12.0 V 1.5 A 18.0 W         | 82.8 % |
| C port + Q port DC 5.0 V 3.5 A 17.5 W | 82.8 % |

|                           |        |
|---------------------------|--------|
| No-load power consumption | 0.09 W |
|---------------------------|--------|

|                    |            |
|--------------------|------------|
| Charging standards |            |
| Power Delivery     | USB 3.1 PD |

## Schutzeinrichtungen

### Thermische Sicherungen

|                    |                                  |
|--------------------|----------------------------------|
| Bemessungsspannung | 230 V~                           |
| Bemessungsstrom    | 10 A                             |
| Typ                | Bimetallsicherung (rückstellbar) |

## Protective devices

### Fuses

|               |                          |
|---------------|--------------------------|
| Rated voltage | 230 V~                   |
| Rated current | 10 A                     |
| Type          | Bimetal fuse (resetable) |

## Weitere Produkteigenschaften

|           |                |
|-----------|----------------|
| Plattform | Standard (kHE) |
|-----------|----------------|

### Material

Gehäuse:  
Aluminium, eloxiert

Abdeckung:  
AKROMID® NEXT 5.6 3 GF 30 FR,  
schwarz

### Lieferumfang

1x CYCLE Desk Steckdosenleiste

Im Karton

## Further product attributes

|           |                |
|-----------|----------------|
| Plattform | Standard (kHE) |
|-----------|----------------|

### Material

Housing:  
Aluminium, anodised

Cover:  
AKROMID® NEXT 5.6 3 GF 30 FR, black

### Scope of delivery

1x CYCLE Desk power strip

In carton

## Umgebungsbedingungen

|                                                 |                |
|-------------------------------------------------|----------------|
| Maximale Höhe                                   | 2000 m         |
| Umgebungstemperatur bei Montage und Nutzung     | 5 °C – 35 °C   |
| Vor direkter Sonneneinstrahlung schützen.       |                |
| Umgebungstemperatur bei Transport und Lagerung  | -20 °C - 60 °C |
| Relative Luftfeuchtigkeit (nicht kondensierend) | 10 % – 90 %    |
| Schutzart                                       | IP20           |

## Environmental conditions

|                                                      |                |
|------------------------------------------------------|----------------|
| Maximum height                                       | 2000 m         |
| Surrounding temperature during mounting and use      | 5 °C – 35 °C   |
| Protect from direct sunlight.                        |                |
| Surrounding temperature during transport and storage | -20 °C - 60 °C |
| Relative humidity (non-condensing)                   | 10 % – 90 %    |
| Protection type                                      | IP20           |

| Konformität | Conformity |
|-------------|------------|
|-------------|------------|

|                          |                                                       |                          |                                                       |
|--------------------------|-------------------------------------------------------|--------------------------|-------------------------------------------------------|
| <b>Angewandte Normen</b> | IEC 62368-1 (USB-Charger)<br>EN 62368-1 (USB-Charger) | <b>Applied standards</b> | IEC 62368-1 (USB-Charger)<br>EN 62368-1 (USB-Charger) |
|--------------------------|-------------------------------------------------------|--------------------------|-------------------------------------------------------|