

Datenblatt Art. BM0022779

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

CONNECTUS

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung Frequenz	16A / 250V~ 50Hz	Rated current / rated voltage Frequency	16A / 250V~ 50Hz
Netzanschluss		Power supply	
Zuleitung	2,0m H05VV-F 3G1,5mm²	Supply cable	2,0m H05VV-F 3G1,5mm²
Farbe Zuleitung	Schwarz	Colour supply cable	Black
Stecker	CEE 7/7 (Type E/F)	Plug	CEE 7/7 (Type E/F)
Stromausgang		Power output	
Steckdosen 6x CEE 7/5 (Type E) 2-polig mit Schutzkontakt Mit erhöhtem Berührungsschutz Schwarz, ähnlich RAL 9005, 35° 16 A / 250 V~, IP20		Socket outlets 6x CEE 7/5 (Type E) 2-pole with earthing contact With shutter Black, similar to RAL 9005, 35° 16 A / 250 V~, IP20	
Funktionsmodule		Function modules	
Schalter 2-polig		Switch 2-pole	
Custom Module USB C Charger 65 W (42,5 mm) Ausgangsspannung / Ausgangsstrom / Ausgangsleistung C1 oder C2 (Single Mode)		Custom Modules USB C Charger 65 W (42,5 mm) Output voltage / Output current / Output power C-port C1 or C2 (single mode)	
	DC 5.0 V 3.0 A 15.0 W		DC 5.0 V 3.0 A 15.0 W
	DC 9.0 V 3.0 A 27.0 W		DC 9.0 V 3.0 A 27.0 W
	DC 15.0 V 3.5 A 52.5 W		DC 15.0 V 3.5 A 52.5 W
	DC 20.0 V 3.25 A 65.0 W		DC 20.0 V 3.25 A 65.0 W
	DC PPS: 3.3 V - 21.0 V 3.0A (max. 63.0 W)		DC PPS: 3.3 V - 21.0 V 3.0A (max. 63.0 W)

Ausgangsspannung / Ausgangsstrom / Ausgangsleistung C1-Port (Beide Ausgänge/Dual Mode)	DC 5.0 V 3.0 A 15.0 W DC 9.0 V 3.0 A 27.0 W DC 15.0 V 3.0 A 45.0 W DC 20.0 V 2.25 A 45.0 W DC PPS: 3.3 V - 21.0 V 2.2A (max. 45.0 W)	Output voltage / Output current / Output power C1-port (both outputs/dual mode)	DC 5.0 V 3.0 A 15.0 W DC 9.0 V 3.0 A 27.0 W DC 15.0 V 3.0 A 45.0 W DC 20.0 V 2.25 A 45.0 W DC PPS: 3.3 V - 21.0 V 2.2A (max. 45.0 W)
Ausgangsspannung / Ausgangsstrom / Ausgangsleistung C2-Port (Beide Ausgänge/Dual Mode)	DC 5.0 V 3.0 A 15.0 W DC 9.0 V 2.2 A 20.0 W DC 15.0 V 1.3 A 19.5 W DC 20.0 V 1.0 A 20.0 W DC PPS: 3.3 V - 21.0 V 1.0A (max. 20.0 W)	Output voltage / Output current / Output power C2-port (both outputs/dual mode)	DC 5.0 V 3.0 A 15.0 W DC 9.0 V 2.2 A 20.0 W DC 15.0 V 1.3 A 19.5 W DC 20.0 V 1.0 A 20.0 W DC PPS: 3.3 V - 21.0 V 1.0A (max. 20.0 W)
Durchschnittseffizienz		Average active efficiency	
DC 5.0 V 3.0 A 15.0 W	82.0 %	DC 5.0 V 3.0 A 15.0 W	82.0 %
DC 9.0 V 3.0 A 27.0 W	86.0 %	DC 9.0 V 3.0 A 45.0 W	86.0 %
DC 15.0 V 3.5 A 52.5 W	89.0 %	DC 15.0 V 3.0 A 45.0 W	89.0 %
DC 20.0 V 3.25 A 65.0 W	90.0 %	DC 20.0 V 3.25 A 65.0 W	90.0 %
Effizienz bei niedriger Last (10 %)		Efficiency at low load (10 %)	
DC 5.0 V 3.0 A 15.0 W	63.0 %	DC 5.0 V 3.0 A 15.0 W	63.0 %
DC 9.0 V 3.0 A 27.0 W	69.0 %	DC 9.0 V 3.0 A 45.0 W	69.0 %
DC 15.0 V 3.5 A 52.5 W	78.0 %	DC 15.0 V 3.0 A 45.0 W	78.0 %
DC 20.0 V 3.25 A 65.0 W	79.0 %	DC 20.0 V 3.25 A 65.0 W	79.0 %
Ladestandard Power Delivery	USB 3.0 PD	Charging standards Power Delivery	USB 3.0 PD

Weitere Produkteigenschaften		Further product attributes	
Plattform	Standard (kHE)	Plattform	Standard (kHE)
Material		Material	
Gehäuse: PA6 GF30 850°C, schwarz		Housing: PA6 GF30 850°C, grey	
Abdeckung: PA6 GF30 850°C, schwarz		Cover: PA6 GF30 850°C, grey	
Endkappen: PA6 GF30 850°C, schwarz ähnlich RAL 9005		Endcaps: PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang		Scope of delivery	
1x CONNECTUS Steckdosenleiste		1x CONNECTUS power strip	
Im Polybeutel		Packed in polybag	
Umgebungsbedingungen		Environmental conditions	
Schutzart	IP20	Protection type	IP20