

Q-port DC 9.0 V 2.0 A 18.0 W	80.2 %	Q-port DC 9.0 V 2.0 A 18.0 W	80.2 %
Q-port DC 12.0 V 1.5 A 18.0 W	77.7 %	Q-port DC 12.0 V 1.5 A 18.0 W	77.7 %
C port + Q port DC 5.0 V 3.5 A 17.5 W	81.2 %	C port + Q port DC 5.0 V 3.5 A 17.5 W	81.2 %
Leistungsaufnahme bei Nulllast	0.07 W	No-load power consumption	0.07 W

Weitere Produkteigenschaften

Plattform PIX

Zur Befestigung an einem Möbelstück

Material

Gehäuse:
PA6 GF30 850°C, schwarz ähnlich RAL 9005

Zierring:
PC ABS, schwarz ähnlich RAL 9005

Lieferumfang

1x PIX HOLDER DOUBLE inkl. PIX
Steckdose montiert
1x Zierring montiert, schwarz

Mit POS Verpackung

Further product attributes

Plattform PIX

for fixing to a furniture item

Material

Housing:
PA6 GF30 850°C, black similar to RAL 9005

Ring for embellishment:
PC ABS, black similar to RAL 9005

Scope of delivery

1x PIX HOLDER DOUBLE incl. PIX power
strip installed
1x ring for embellishment mounted, black

With POS packaging

Umgebungsbedingungen

Maximale Höhe	0 - 2000m
Umgebungstemperatur bei Montage und Nutzung	0°C – 35°C
Vor direkter Sonneneinstrahlung schützen.	
Umgebungstemperatur bei Transport und Lagerung	-20°C - 60°C
Relative Luftfeuchtigkeit (nicht kondensierend)	10 – 90%
Luftdruck	80-108 kPa
Schutzart	IP20

Environmental conditions

Maximum height	0 - 2000m
Surrounding temperature during mounting and use	0°C – 35°C
Protect from direct sunlight.	
Surrounding temperature during transport and storage	-20°C - 60°C
Relative humidity (non-condensing)	10 – 90%
Air pressure	80-108 kPa
Protection type	IP20

Konformität

Angewandte Normen	IEC 62368-1 (USB-Charger) EN 62368-1 (USB-Charger)
--------------------------	---

Conformity

Applied standards	IEC 62368-1 (USB-Charger) EN 62368-1 (USB-Charger)
--------------------------	---