



Note:  
 1. ROHS 2.0 Compliant and REACH Compliant  
 2. The out jacket is conform to IEC60332-1, EN60754-2, EN 61034-2  
 3. Min. Bending Radius:Static:12mm Dynamic:24mm

Test:  
 Grade Designation:Each to Reference

Type	Multi-Mode
Insertion Loss	≤0.3dB
Return Loss	≥30dB
Test Wavelength	850nm

**MATERIAL LIST:**

⑧	Ring 1、2	4pcs	
⑦	Black Heat Shrink Tube	2pcs	
⑥	LC Clip Erika violet	2pcs	
⑤	LC Dust Cap White	4pcs	
④	LC Duplex Connector Erika violet	4pcs	
③	LC 1.2 white short boot	4pcs	
②	LC/UPC MM Ceramic Ferrule	4pcs	
①	Fiber Optical Cable Erika violet (RAL4003) 50/125 OM4 Duplex φ1.2mm LSZH	L+100	
NO.	SPECIFICATION STANDARD	QT' Y	REMARK

ITEM NO.	DESC.
21. 15. 9261	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 1m
21. 15. 9262	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 2m
21. 15. 9263	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 3m
21. 15. 9264	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 5m
21. 15. 9266	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 7m
21. 15. 9265	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 10m

		Add Min. Bending Radius	2022-1-24	A1
		NEW	2017-7-17	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

