



NOTE:

1. ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
2. FLUKE Channel LINK TEST:
TEST LIMIT:ISO11801 Channel Class E(+ALL)
3. Working temperature:-10°C~+60°C
Storage temperature:-20°C~+75°C
4. RoHS AND REACH compliant
5. Spray WORD:CAT6 S/FTP 4x2x26AWG/7 PVC ISO11801 & EN50173 & ANSI/TIA568.2-D
6. Support IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt (TYPE 3 & TYPE 4)
7. Minimum of the bending radius is 6*ODmm(Suitable for all meters)

MATERIAL LIST

③	OVER MOLD	75A PVC Gray(RAL 7035)	2	
②	CONNECTOR	RJ45 8P8C SHIELDED, THE SHELL PLATED NICKEL, PIN GOLD PLATED 50u" COLOUR: TRANSPARENT	2	
①	CABLE	CAT. 6 S/FTP 26AWG (BC*1P+AL-FOLL)*4PAIRS+BRAID (AL-MG) JACKET:PVC Gray(RAL 7035) OD:6.0±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

21.51.1310	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, grey, 0.3m	300±20
21.51.0830	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, grey, 0.5m	500±20
21.51.0831	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, grey, 1m	1000±20
21.51.0823	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, grey, 1.5m	1500±30
21.51.0832	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, grey, 2m	2000±30
21.51.0833	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, grey, 3m	3000±50
21.51.0835	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, grey, 5m	5000±100
21.51.0837	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, grey, 7m	7000±200
21.51.0840	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, grey, 10m	10000±200
21.51.0845	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, grey, 15m	15000±300
21.51.0850	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, grey, 20m	20000±300
ITEM NO.	DESC.	LENGTH

ARVIN		NEW	2025-10-16	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

