



NOTE:

- ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
- FLUKE Channel LINK TEST:
TEST LIMIT:ISO11801 Channel Class E(+ALL)
- Working temperature:-10°C~+60°C
Storage temperature:-20°C~+75°C
- RoHS AND REACH compliant
- Spray WORD:CAT6 S/FTP 4x2x26AWG/7 PVC ISO11801 & EN50173 & ANSI/TIA568.2-D
- Support IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt (TYPE 3 & TYPE 4)
- Minimum of the bending radius is 6*ODmm(Suitable for all meters)

MATERIAL LIST

NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
③	OVER MOLD	75A PVC Red(Pantone 199C)	2	
②	CONNECTOR	RJ45 8P8C SHIELDED, THE SHELL PLATED NICKEL, PIN GOLD PLATED 50u" COLOUR: TRANSPARENT	2	
①	CABLE	CAT. 6 S/FTP 26AWG (BC*1P+AL-FOLL)*4PAIRS+BRAID (AL-MG) JACKET:PVC Red(Pantone 199C) OD:6.0±0.2mm	1	

ITEM NO.	DESC.	LENGTH
21.51.1311	ROLINE S/FTP(PiMF) PatchCord Cat.6/Class E, red, 0.3m	300±20
21.51.1321	ROLINE S/FTP(PiMF) PatchCord Cat.6/Class E, red, 0.5m	500±20
21.51.1331	ROLINE S/FTP(PiMF) PatchCord Cat.6/Class E, red, 1m	1000±20
21.51.0824	ROLINE S/FTP(PiMF) PatchCord Cat.6/Class E, red, 1.5m	1500±30
21.51.1341	ROLINE S/FTP(PiMF) PatchCord Cat.6/Class E, red, 2m	2000±30
21.51.1351	ROLINE S/FTP(PiMF) PatchCord Cat.6/Class E, red, 3m	3000±50
21.51.1361	ROLINE S/FTP(PiMF) PatchCord Cat.6/Class E, red, 5m	5000±100
21.51.1371	ROLINE S/FTP(PiMF) PatchCord Cat.6/Class E, red, 7m	7000±200
21.51.1381	ROLINE S/FTP(PiMF) PatchCord Cat.6/Class E, red, 10m	10000±200
21.51.1391	ROLINE S/FTP(PiMF) PatchCord Cat.6/Class E, red, 15m	15000±300
21.51.1401	ROLINE S/FTP(PiMF) PatchCord Cat.6/Class E, red, 20m	20000±300

ARVIN		NEW	2025-10-16	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

