



NOTE:

1. ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
2. FLUKE Channel LINK TEST:
TEST LIMIT:ISO11801 Channel Class E(+ALL)
3. Working temperature:-10°C~+60°C
Storage temperature:-20°C~+75°C
4. RoHS AND REACH compliant
5. Spray WORD:CAT6 S/FTP 4x2x26AWG/7 PVC ISO11801 & EN50173 & ANSI/TIA568.2-D
6. Support IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt (TYPE 3 & TYPE 4)
7. Minimum of the bending radius is 6*ODmm(Suitable for all meters)

MATERIAL LIST

③	OVER MOLD	75A PVC Green(Pantone 3278C)	2	
②	CONNECTOR	RJ45 8P8C SHIELDED, THE SHELL PLATED NICKEL, PIN GOLD PLATED 50u" COLOUR: TRANSPARENT	2	
①	CABLE	CAT. 6 S/FTP 26AWG (BC*1P+AL-FOLL)*4PAIRS+BRAID (AL-MG) JACKET:PVC Green(Pantone 3278C) OD:6.0±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

21. 51. 1313	ROLINE S/FTP (PiMF) PatchCord Cat. 6/Class E, green, 0. 3m	300±20
21. 51. 1323	ROLINE S/FTP (PiMF) PatchCord Cat. 6/Class E, green, 0. 5m	500±20
21. 51. 1333	ROLINE S/FTP (PiMF) PatchCord Cat. 6/Class E, green, 1m	1000±20
21. 51. 0826	ROLINE S/FTP (PiMF) PatchCord Cat. 6/Class E, green, 1. 5m	1500±30
21. 51. 1343	ROLINE S/FTP (PiMF) PatchCord Cat. 6/Class E, green, 2m	2000±30
21. 51. 1353	ROLINE S/FTP (PiMF) PatchCord Cat. 6/Class E, green, 3m	3000±50
21. 51. 1363	ROLINE S/FTP (PiMF) PatchCord Cat. 6/Class E, green, 5m	5000±100
21. 51. 1373	ROLINE S/FTP (PiMF) PatchCord Cat. 6/Class E, green, 7m	7000±200
21. 51. 1383	ROLINE S/FTP (PiMF) PatchCord Cat. 6/Class E, green, 10m	10000±200
21. 51. 1393	ROLINE S/FTP (PiMF) PatchCord Cat. 6/Class E, green, 15m	15000±300
21. 51. 1403	ROLINE S/FTP (PiMF) PatchCord Cat. 6/Class E, green, 20m	20000±300
ITEM NO.	DESC.	LENGTH

ARVIN		NEW	2025-10-16	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

