



NOTE:

- ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
- FLUKE Channel LINK TEST:
TEST LIMIT:ISO11801 Channel Class E(+ALL)
- Working temperature: $-10^{\circ}\text{C} \sim +60^{\circ}\text{C}$
Storage temperature: $-20^{\circ}\text{C} \sim +75^{\circ}\text{C}$
- RoHS AND REACH compliant
- Spray WORD:CAT6 S/FTP 4x2x26AWG/7 PVC ISO11801 & EN50173 & ANSI/TIA568.2-D
- Support IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt (TYPE 3 & TYPE 4)
- Minimum of the bending radius is $6 * OD \text{mm}$ (Suitable for all meters)

MATERIAL LIST

③	OVER MOLD	75A PVC Black(Pantone 3C)	2	
②	CONNECTOR	RJ45 8P8C SHIELDED, THE SHELL PLATED NICKEL, PIN GOLD PLATED 50u" COLOUR: TRANSPARENT	2	
①	CABLE	CAT. 6 S/FTP 26AWG (BC*1P+AL-FOLL)*4PAIRS+BRAID (AL-MG) JACKET:PVC Black(Pantone 3C) OD:6.0±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

21.51.1315	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, black, 0.3m	300±20
21.51.1325	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, black, 0.5m	500±20
21.51.1335	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, black, 1m	1000±20
21.51.0828	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, black, 1.5m	1500±30
21.51.1345	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, black, 2m	2000±30
21.51.1355	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, black, 3m	3000±50
21.51.1365	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, black, 5m	5000±100
21.51.1375	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, black, 7m	7000±200
21.51.1385	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, black, 10m	10000±200
21.51.1395	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, black, 15m	15000±300
21.51.1405	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, black, 20m	20000±300
ITEM NO.	DESC.	LENGTH

ARVIN		NEW	2025-10-16	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

