



NOTE:

1. ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
2. FLUKE Channel LINK TEST:
TEST LIMIT:ISO11801 Channel Class E(+ALL)
3. Working temperature:-10°C~+60°C
Storage temperature:-20°C~+75°C
4. RoHS AND REACH compliant
5. Spray WORD:CAT6 S/FTP 4x2x26AWG/7 PVC ISO11801 & EN50173 & ANSI/TIA568.2-D
6. Support IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt (TYPE 3 & TYPE 4)
7. Minimum of the bending radius is 6*ODmm(Suitable for all meters)

MATERIAL LIST

③	OVER MOLD	75A PVC White (RAL9003)	2	
②	CONNECTOR	RJ45 8P8C SHIELDED, THE SHELL PLATED NICKEL, PIN GOLD PLATED 50u" COLOUR: TRANSPARENT	2	
①	CABLE	CAT. 6 S/FTP 26AWG (BC*1P+AL-FOLL)*4PAIRS+BRAID (AL-MG) JACKET:PVC White (RAL9003) OD:6.0±0.2mm	1	

NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
	ARVIN	NEW	2025-10-16	A
	BY	CHK	REVISION RECORD MODIFICATIONS	DATE
				REV.

ITEM NO.	DESC.	LENGTH
21.51.1316	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, white, 0.3m	300±20
21.51.1326	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, white, 0.5m	500±20
21.51.1336	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, white, 1m	1000±20
21.51.0829	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, white, 1.5m	1500±30
21.51.1346	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, white, 2m	2000±30
21.51.1356	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, white, 3m	3000±50
21.51.1366	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, white, 5m	5000±100
21.51.1376	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, white, 7m	7000±200
21.51.1386	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, white, 10m	10000±200
21.51.1396	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, white, 15m	15000±300
21.51.1406	ROLINE S/FTP (PiMF) PatchCord Cat.6/Class E, white, 20m	20000±300

