



Notes:

Electrical:

1. Voltage Rating: 125 VAC RMS
2. Current Rating: 1.5AMP
3. Contact Resistance: 100 MILLIOHMS Max
4. Insulation Resistance: 1000 MEGOHMS Min @500 VDC
5. Dielectric Strength: 750 VAC RMS 60Hz, 1MIN

Environmental:

1. Storage Temperature: -40°C ~ +85°C
2. Operation Temperature: 0°C ~ +70°C

Mechanical:

1. Housing Material: PA66
2. Insert Material: ABS
3. PCB Material: FR-4 T=1.6mm
4. RJ45 Jack Contact: Phosphor Bronze with Nickel Plated Shell and Gold Plated Pin 3u"
5. RJ45 Jack Life: 750 Times Min.
6. Waterproof Grade: IP68

					VALUE RJ45 Coupler, CAT.6A, STP, Dust- / Waterproof, black			
					Item No. 21.99.3007			
SYM	Number	Bill No.of Alteration	Signature	Date	Angles Projection	Size	Scale	Unit
Drawn	Kevin	2019.3.5				A4	X:1	mm
				Tolerance				
				0.00-20.00 ±0.10				
				20.00-50.00 ±0.15				
				50.00-100.00 ±0.20				
				100.00- ±0.25				
				Angle ±30				
Approved	Wang wei jun	2019.3.5			Sheet	1 OF 1	Version: A/0	

