


Note:

1. ROHS 2.0 & REACH Compliant
2. The out jacket is conform to IEC60332-1, EN60754-2, EN 61034-2
3. Min. Bending Radius: Static: 20mm, Dynamic: 40mm

Test:

Grade Designation: Each to Reference



TYPE	MULTI-MODE
Insertion Loss	≤0.15dB (IEC 61300-3-4)
Return Loss	>30dB (IEC 61300-3-6)
Test Wavelength	850nm

⑧	Ring 1 2 Yellow	4pcs	
⑦	Black Heat Shrink Tube	2pcs	
⑥	LC MM Aqua Clip	2pcs	
⑤	LC Dust Cap White	4pcs	
④	LC Aqua Duplex Connector	4pcs	
③	LC White Boot	4pcs	
②	LC Ferrule 126-128um	4pcs	
①	Fiber Optical Cable Duplex $\phi$ 2.0mm OM3-300 50/125um Aqua LSZH	L+0.1m	
NO.	SPECIFICATION STANDARD	QT' Y	REMARK

21.99.8827	VALUE FO Jumper Cable, 50/125 $\mu$ m OM3, LC-LC, Low-Loss, 20m
21.99.8826	VALUE FO Jumper Cable, 50/125 $\mu$ m OM3, LC-LC, Low-Loss, 15m
21.99.8825	VALUE FO Jumper Cable, 50/125 $\mu$ m OM3, LC-LC, Low-Loss, 10m
21.99.8824	VALUE FO Jumper Cable, 50/125 $\mu$ m OM3, LC-LC, Low-Loss, 5m
21.99.8823	VALUE FO Jumper Cable, 50/125 $\mu$ m OM3, LC-LC, Low-Loss, 3m
21.99.8822	VALUE FO Jumper Cable, 50/125 $\mu$ m OM3, LC-LC, Low-Loss, 2m
21.99.8821	VALUE FO Jumper Cable, 50/125 $\mu$ m OM3, LC-LC, Low-Loss, 1m
21.99.8820	VALUE FO Jumper Cable, 50/125 $\mu$ m OM3, LC-LC, Low-Loss, 0.5m

ITEM NO. DESC.

		NEW	2019-8-26	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

**SECOMP**