

TP-Link Tapo C210 Dome IP-beveiligingscamera Binnen 1920 x 1080 Pixels Plafond/bureau

Merk : TP-Link

Productfamilie: Tapo

Artikelcode: TAPO C210

Productnaam : C210

TP-Link Tapo C210. Soort: IP-beveiligingscamera, Ondersteuning voor plaatsing: Binnen, Connectiviteitstechnologie: Draadloos. Montagewijze: Plafond/bureau, Kleur van het product: Wit, Vormfactor: Dome. Draaihoek: 360°, Bereik kantelhoek: 0 - 114°, Pan bereik: 0 - 360°. Omvang optische sensor: 25,4 / 2,9 mm (1 / 2.9"). Vaste focale lengte: 4 mm



Prestatie		Netwerk	
Soort *	IP-beveiligingscamera	Ethernet LAN *	✗
Ondersteuning voor plaatsing *	Binnen	Netwerkstandaard	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Connectiviteitstechnologie *	Draadloos	Wifi *	✓
Certificering	FCC, IC, CE, NCC	Wi-Fi-standaarden	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Design		Bluetooth *	✗
Vormfactor *	Dome	Opslagmedia	
Montagewijze *	Plafond/bureau	Ingebouwde HDD *	✗
Kleur van het product *	Wit	Compatibele geheugenkaarten	MicroSD (TransFlash)
LED-indicatoren	Systeem	Poorten & interfaces	
Camera		Aansluiting voor netstroomadapter	✓
Draaihoek	360°	Beveiliging	
Bereik kantelhoek	0 - 114°	Ondersteunde beveiligingsalgoritmen	WPA, WPA2-PSK
Pan bereik	0 - 360°	Energie	
Beeldsensor		Type stroombron *	AC, DC
Aantal sensoren	1	AC-ingangsspanning	100 - 240 V
Omvang optische sensor	25,4 / 2,9 mm (1 / 2.9")	AC-ingangsfrequentie	50 - 60 Hz
Lenssysteem		Stroomverbruik	300 mA
Aantal lenzen *	1	Stroomuitvoer (volt)	9
Vaste focale lengte	4 mm	Stroomuitvoer (ampère)	0,6 A
Nachtkijker		Eisen aan de omgeving	
Nachtvisie *	✓	Bedrijfstemperatuur (T-T)	0 - 40 °C
Nachtkijker afstand	9.144 m	Temperatuur bij opslag	-40 - 70 °C
LED-type	IR	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Infrarood wavelength	850 nm	Luchtvochtigheid bij opslag	5 - 90 procent
Video		Gewicht en omvang	
Maximum resolutie *	1920 x 1080 Pixels	Breedte	86,6 mm
Totaal aantal megapixels *	3 MP	Diepte	85 mm
Ondersteunde videoformaten	H.264	Hoogte	117,7 mm
Videocompressieformaten	H.264	Inhoud van de verpakking	
Ondersteunde grafische resoluties	1920 x 1080 (HD 1080)	Aantal cameras *	1
Ondersteunde video-modi	1080p	Montage gereedschap	✓
Maximaal 30 frames per seconde	15 fps	Gebruikershandleiding	✓
Audio		Logistieke gegevens	
Ingebouwde luidsprekers	✓	Code geharmoniseerd systeem (HS) 85258900	
Audiosysteem	2-weg		
Ingebouwde microfoon	✓		



4897098682753



4897098682777

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-MAY-2023. Prints or copies of Information are only valid on the printed Publication date