

Brother PT-E560BTSP labelprinter Thermo transfer 180 x 180 DPI 30 mm/sec Bedraad en draadloos HSE/TZe Bluetooth QWERTZ

Merk : Brother

Artikelcode: PTE560BTSPR

Productnaam : PT-E560BTSP

Brother PT-E560BTSP. Toetsenbordindeling: QWERTZ. Soort tape: HSE/TZe. Printtechnologie: Thermo transfer, Maximale resolutie: 180 x 180 DPI, Printsnelheid (metrisch): 30 mm/sec. Connectiviteitstechnologie: Bedraad en draadloos. Type batterij: Ingebouwde accu, Batterijtechnologie: Lithium-ion (Li-Ion). Kleur van het product: Zwart, Oranje



Printing		Power	
Print technology *	Thermal transfer	Number of batteries supported	1
Colour *	✗	Battery technology	Lithium-Ion (Li-Ion)
Maximum resolution *	180 x 180 DPI	Auto power off	✓
Number of printable dots	128 dot	Power source type	Battery
Print speed *	30 mm/sec	Battery	
Maximum printing width *	2.4 cm	Rechargeable battery	✓
Maximum print height	1.8 cm	System requirements	
Vertical printing	✓	Windows operating systems supported	Windows 10, Windows 11
Mirror printing	✓	Mac operating systems supported	Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Rotated printing	✓	Mobile operating systems supported	Android 10, Android 9.0, iOS 11.0, iOS 12, iOS 13, iOS 15, iOS 16
Paper handling		Weight & dimensions	
Autocutter	✓	Width	132 mm
Half-cutter	✓	Depth	244 mm
Ports & interfaces		Height	80 mm
Connectivity technology *	Wired & Wireless	Weight	1.05 kg
Ethernet LAN *	✗	Packaging data	
Wi-Fi *	✗	Package width	126 mm
Bluetooth	✓	Package depth	334.4 mm
Bluetooth version	5.0	Package height	393 mm
USB port *	✓	Package weight	3.1 kg
Performance		Packaging content	
Built-in barcodes	CODABAR (NW-7), Code 128 (A/B/C), Code 39, Data Matrix, EAN13, GS1-128, UPC-A, UPC-E	Cables included	USB
Number of symbols	476	Batteries included	✓
Number of characters	684		
Number of fonts	14		

Performance		Packaging content	
Tape type	HSE/TZe	Quick start guide	✓
Number of printing lines (max)	7	Warranty card	✓
Underline	✓	Wrist strap included	✓
Design		Technical details	
Product colour *	Black, Orange	Multi-block	99
Keyboard number of keys	70	PC connection	USB 3.2 Gen 1 (3.1 Gen 1)
Built-in display	✓	Other features	
Display *	LCD	Memory capacity	1800 characters
Backlight display	✓	Print preview	✓
Keyboard layout	QWERTZ	Label memory	99 label(s)
Power		Number of frames	7
Battery type	Built-in battery	Languages support	Multi



4977766835732

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-FEB-2025. Prints or copies of Information are only valid on the printed Publication date