

TP-Link TL-R480T+ bedrade router Zwart

Merk: TP-Link Artikelcode: TL-R480T+

Productnaam: TL-R480T+





WAN connection		Security	
Ethernet WAN *	✓	DoS attack prevention	✓
Network		Access Control List (ACL)	✓
Networking standards *	IEEE 802.3, IEEE 802.3u, IEEE 802.3x 10/100Base-T(X) 10,100 Mbit/s ✓	IP-MAC-Port binding	✓
Cabling technology		Features	
Ethernet LAN data rates Static route		Professional x64, Windows 7	128 MB Windows 2000, Windows 7 Enterprise, Windows 7 Enterprise
VLAN support	/		
Auto MDI/MDI-X	X		·
Policy-based routing	✓		Windows 7 Home Premium x64, Windows 7 Professional, Windows 7
Mobile network			
Mobile network generation	Not supported		Professional x64, Windows 7 Starter, Windows 7 Starter x64,
Management features			Windows 7 Ultimate, Windows 7
Web-based management * Quality of Service (QoS) support Universal Plug and Play (UPnP) Reset button Firmware upgradeable Ports & interfaces Ethernet LAN (RJ-45) ports * Fiber ports quantity DC-in jack	6 1	x64, Windows Vista Enterprise : Windows Vista Enterprise : Windows Vista Home Basic Windows Vista Home Basic Windows Vista Home Prem Windows Vista Home Prem Windows Vista Ultimate, W Vista Ultimate x64, Window Home, Windows XP Home	Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Protocols		Linux operating systems supported	✓
DMZ support	✓	Minimum system requirements	1
Management protocols	SNTP, HTTP	Design	
DHCP client *	✓	Product colour *	Black
DHCP server *	/	Rack mounting	✓
Supported network protocols	TCP/IP, DHCP, ICMP	Rack capacity	1U
Security		LED indicators	LAN, Power, Status, WAN
Security algorithms *	IPSec	Power	
MAC address filtering	✓	AC input voltage	100 - 240 V
URL filtering	✓	AC input frequency	50 - 60 Hz
IP address filtering	✓	Operational conditions	
		Operating temperature (T-T)	0 - 40 °C

Operational conditions	
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	294 mm
Depth	180 mm
Height	44 mm
Other features	

Unmanaged

Switch type



5996409097503

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.