## NETGEAR MS105-100EUS netwerk-switch Unmanaged 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE) 1U

Merk: NETGEAR Artikelcode: MS105-100EUS

**Productnaam:** MS105-100EUS



NETGEAR MS105-100EUS. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: 2.5G Ethernet (100/1000/2500), Aantal basis-switching RJ-45 Ethernet-poorten: 5. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 25 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3, IEEE 802.3az, IEEE 802.3x. DC voltage input: 12 V. Power over Ethernet (PoE). Rack-montage, Vormfactor: 1U

Beheerfuncties		Design	
Switch type *	Unmanaged	Vormfactor	10
Poorten & interfaces		Energie	
Aantal basis-switching RJ-45 Ethernet-poorten *	5	Stroombron * Vermogenstoevoer inclusief *	DC ✓
Type basis-switching RJ-45 Ethernet-poorten *	2.5G Ethernet (100/1000/2500)	DC voltage input Stroomverbruik (typisch)	12 V 9,24 W
Netwerk		Power over Ethernet (PoE)	
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3, IEEE 802.3az, IEEE 802.3x	Power over Ethernet (PoE) *	✓
10G support *	×	Eisen aan de omgeving	
10G support *  Data-uitwisseling	×	<b>Eisen aan de omgeving</b> Bedrijfstemperatuur (T-T)	0 - 40 °C
Data-uitwisseling Switchingcapaciteit *	25 Gbit/s	, ,	0 - 40 °C 0 - 95 procent
Data-uitwisseling Switchingcapaciteit * MAC-adrestabel *	25 Gbit/s 16000 entries	Bedrijfstemperatuur (T-T) Relatieve vochtigheid in bedrijf (V-	
Data-uitwisseling Switchingcapaciteit * MAC-adrestabel * Packet forwarding rate (1 Gbps)	25 Gbit/s	Bedrijfstemperatuur (T-T) Relatieve vochtigheid in bedrijf (V- V)	0 - 95 procent
Data-uitwisseling Switchingcapaciteit * MAC-adrestabel * Packet forwarding rate (1 Gbps) Design	25 Gbit/s 16000 entries	Bedrijfstemperatuur (T-T) Relatieve vochtigheid in bedrijf (V-V) Hoogte, in bedrijf	0 - 95 procent
Data-uitwisseling Switchingcapaciteit * MAC-adrestabel * Packet forwarding rate (1 Gbps)  Design Rack-montage *	25 Gbit/s 16000 entries	Bedrijfstemperatuur (T-T) Relatieve vochtigheid in bedrijf (V-V) Hoogte, in bedrijf Gewicht en omvang	0 - 95 procent 0 - 3000 m
Data-uitwisseling Switchingcapaciteit * MAC-adrestabel * Packet forwarding rate (1 Gbps) Design	25 Gbit/s 16000 entries	Bedrijfstemperatuur (T-T) Relatieve vochtigheid in bedrijf (V-V) Hoogte, in bedrijf  Gewicht en omvang Breedte	0 - 95 procent 0 - 3000 m





606449160093

0606449160093



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.