

NETGEAR M4350-32F8V Managed L3 1U Zwart

Merk : NETGEAR

Artikelcode: XSM4340FV-100NES

Productnaam : M4350-32F8V

NETGEAR M4350-32F8V. Switch type: Managed, Switch-laag: L3. Full duplex. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 1040 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qav, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... Netstekker: AC-in-aansluiting. Rack-montage, Vormfactor: 1U




Beheerfuncties		Beveiliging	
Switch type *	Managed	Algoritmen wachtrijplanning	Strict Priority Queue (SPQ), Weighted random early detection (WRED)
Switch-laag	L3		
Quality of Service (QoS)	✓		
Web-gebaseerd management	✓		
ARP-inspectie	✓		
Poorten & interfaces		Multicast-functies	
Type basis-switching RJ-45 Ethernet-poorten *	✗	Multicast-ondersteuning	✓
Aantal moduleslots SPF+	32	Multicast Listener Discovery (MLD) snooping	✓
Aantal SFP28-poorten	8		
Netstekker	AC-in-aansluiting	Protocollen	
Netwerk		Beheerprotocollen	SNMP V1, V2, V3
Netwerkstandaard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qav, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ak, IEEE 802.3bz, IEEE 802.3u	GARP VLAN Registratieprotocol (GVRP)	✓
10G support *	✓	Routing protocols	OSPF, OSPFv2, OSPFv3, RIP, RIP-1, RIP-2
Full duplex	✓	Design	
Op beleid gebaseerde routing	✓	Rack-montage *	✓
Datastroombeheer	✓	Stapelbaar *	✓
Verbindingsaggregatie	✓	Vormfactor	1U
Broadcast stormbeheer	✓	Kleur van het product	Zwart
Rate limiting	✓	LED-indicatoren	✓
Spanning tree protocol	✓	Luchtstroomrichting	Luchtstroom van voren naar achteren
6to4-tunnel	✓	Prestatie	
IPv4-routes	512	Type processor	✓
IPv6-routes	256	Processormodel	ARM Cortex-A57
VLAN=ondersteuning	✓	Frequentie van processor	1800 MHz
Virtuele LAN-functies	MAC address-based VLAN, Private VLAN, Voice VLAN	Type geheugen	DDR4-SDRAM
Aantal VLANs	4093	Intern geheugen	4096 MB
Data-uitwisseling		Flash memory	512 MB
Switchingcapaciteit *	1040 Gbit/s	sFlow	✓
Throughput	773,76 Mpps	Energie	
MAC-adrestabel *	16000 entries	Stroombron *	AC
Store-and-forward	✓	Vermogenstoevoer inclusief *	✓
Latentie (10 Gbps)	1,27 µs	Stroomverbruik (typisch)	156,4 W
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✗

Data-uitwisseling		Eisen aan de omgeving	
Jumbo Frames ondersteuning	✓	Bedrijfstemperatuur (T-T)	0 - 50 °C
Jumbo frames	12000	Temperatuur bij opslag	-20 - 70 °C
Packet buffergeheugen	64 MB	Relatieve vochtigheid in bedrijf (V-V)	0 - 90 procent
Beveiliging		Luchtvochtigheid bij opslag	0 - 95 procent
DHCP-functies	DHCP Option 150, DHCP Option 66, DHCP Option 67, DHCP relay, DHCP server, DHCP snooping	Hoogte, in bedrijf	0 - 3000 m
Access Control List (ACL)	✓	Hoogte bij opslag	0 - 3000 m
Toegangsbeheerlijst (ACL) uitgaand	1023	Gewicht en omvang	
Toegangsbeheerlijst (ACL) inkomend	511	Breedte	440 mm
IGMP snooping	✓	Diepte	400 mm
IGMP-proxy	✓	Hoogte	43,2 mm
MAC adres filtering	✓	Gewicht	6,95 kg
Statische poort beveiliging	✓	Verpakking	
Bescherming lus	✓	Meegeleverde kabels	AC, USB Type-C
BPDU filtering / bescherming	✓	Snelstartgids	✓
Authenticatie	Gast-VLAN, MAC-gebaseerde authenticatie	Rekbevestigingspakket	✓
Root-bescherming	✓	Inbegrepen soorten voedingsstekkers	EU, NA, UK
Wachtwoordbeveiliging	✓	Duurzaamheid	
DoS aanval preventie	✓	Naleving van duurzaamheid	✓
Authenticatie type	RADIUS, TACACS+	Duurzaamheidscertificaten	BSMI, CCC, CE, Federal Communications Commission (FCC), Low Voltage Directive (LVD)
		Overige specificaties	
		Netvoeding	420 W



0606449165166



606449165166

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-MAR-2024. Prints or copies of Information are only valid on the printed Publication date