

NETGEAR ProSAFE Unmanaged Switch - JGS524 - 24 Gigabit Ethernet poorten 10/100/1000 Mbps



Merk : NETGEAR

Artikelcode: JGS524-200EUS

Productnaam : ProSAFE Unmanaged Switch - JGS524 - 24 Gigabit Ethernet poorten 10/100/1000 Mbps

ProSAFE Unmanaged Switch - JGS524 - 24 Gigabit Ethernet poorten 10/100/1000 Mbps
 NETGEAR ProSAFE Unmanaged Switch - JGS524 - 24 Gigabit Ethernet poorten 10/100/1000 Mbps. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 24. Full duplex. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 48 Gbit/s. Netwerkstandaard: IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Rack-montage

| Beheerfuncties | | Prestatie | |
|---|---|--|--------------------|
| Switch type * | Unmanaged | Geluidsniveau | 40 dB |
| Quality of Service (QoS) | ✓ | Mean time between failures (MTBF) | 87600 uur |
| Poorten & interfaces | | Energie | |
| Aantal basis-switching RJ-45 Ethernet-poorten * | 24 | Stroombron * | AC |
| Type basis-switching RJ-45 Ethernet-poorten * | Gigabit Ethernet (10/100/1000) | AC-ingangsspanning | 100 - 240 V |
| | | AC-ingangsfrequentie | 50 - 60 Hz |
| | | Stroomverbruik (typisch) | 17,9 W |
| Netwerk | | Power over Ethernet (PoE) | |
| Netwerkstandaard * | IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x | Power over Ethernet (PoE) * | ✗ |
| 10G support * | ✗ | Eisen aan de omgeving | |
| Full duplex | ✓ | Bedrijfstemperatuur (T-T) | 0 - 50 °C |
| Datastroombeheer | ✓ | Temperatuur bij opslag | -20 - 70 °C |
| Ethernet LAN, data-overdrachtsnelheden | 10,100,1000 Mbit/s | Relatieve vochtigheid in bedrijf (V-V) | 5 - 90 procent |
| | | Luchtvochtigheid bij opslag | 10 - 95 procent |
| Data-uitwisseling | | Gewicht en omvang | |
| Ondersteunde data-overdrachtsnelheden | 10/100/1000 Mbps | Gewicht | 2,4 kg |
| Switchingcapaciteit * | 48 Gbit/s | Logistieke gegevens | |
| MAC-adrestabel * | 8000 entries | Code geharmoniseerd systeem (HS) | 85176990 |
| Max. overdrachtssnelheid | 2 Gbit/s | Overige specificaties | |
| Design | | Latentie | 20 µs |
| Rack-montage * | ✓ | Afmetingen (B x D x H) | 330 x 207 x 43 mm |
| Stapelbaar * | ✗ | Connectiviteitstechnologie | Bedraad |
| Kleur van het product | Blauw | Stroomvoorziening | 100~240V; 50-60Hz; |
| Certificering | CE, FCC 15 A, VCCI A, EN 55022 (CISPR 22) A, EN 50082-1, EN 55024, C-Tick | Connectivity LEDs | ✓ |



0606449064261



606449064261

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.